24-Channel Digital Rack Mixer with Integrated Audio Information Interface

AVB Stagebox mode for StudioLive Series III mixers 24 Microphone / Line inputs XLR / jack 6.3 mm combo sockets with 48 V phantom power

Stereo AUX input RCA (L / R)

16 AUX Sends

12 Mix outputs 6.3 mm jack balanced

2 Main outputs XLR (L / R)

Stereo headphone output 6.3 mm jack

"Mute All" button for muting all inputs and outputs

Integrated SD card recorder (stereo) for recording the

main signal and for use as a player

40x40 USB recording interface

55x55 AVB recording interface

Converter: 24 Bit / 48 kHz with 115 dB dynamic range Fat Channel signal processing: Polarity, high pass filter, gate / expander with sidechain, fully parametric 4-band EQ, compressor with sidechain, limiter, including vintage plug-ins for EQ and compressor

4 Master effects processors including vintage reverb plugins

Line delay in all inputs and outputs

Fully parametric 6-band EQ in all outputs, 8 graphic EQs (31-Band)

Presets plus user memory for Fat Channel, effects and graphic EQ

USB port, Ethernet Control connector, Ethercon AVB audio network connector

Control software "UC Surface" for OS X, Windows, iPad and Android tablet

Free monitor app "QMix-UC" for iPhone, iPod Touch and Android smartphones

Build: 19" / 2 U

Dimensions: 483 x 305 x 90 mm

Weight: 4.9 kg

Includes recording software "Capture", DAW software "Studio One 3 Artist", "Studio Magic" plugin suite and

Further

Max.number of input channels	24
Microphone Inputs	24
Analog Line Inputs	24
Analog Line Outputs	14
Analog in/ out with plug-in card expandable	No
Digital Inputs	AVB Audio Netzwork, USB
Digital Outputs	AVB Audio- Network-Port, USB
Digital in-/ outputs expandable	No
Word Clock	No
Motorfader	No
Computer interface	USB, Ethernet
MIDI-interface	No

Fat Channel Plugin Collection (for download)

System requirements:

Mac OS X 10.8.5 64 bit or newer Windows 7 x64 / x86 SP1 Windows 8 x64 / x86 Windows 10 x64 / x86