

## TECH SPECS

### Technical Data

Speaker Type 2-Way Active Speaker

### Acoustical data

Usable Bandwidth [-10dB] 55 - 20.000 Hz

Frequency Response [-6 dB] 61 - 19.500 Hz

Max SPL 126 dB

Type HF Compression Driver

HF voice coil 1 "

LF 12 "

LF voice coil 2 "

Crossover Frequency 2100 Hz (24 dB/oct.)

Horizontal Dispersion asymmetrical 85° up / 120° down

Vertical Dispersion 85° (+25/ -60°)

### Amplifier

Amp Technology Custom Made

Amp Class Class D - Passive cooling (convection)

Power Peak 400 W

### Processor

Controller DSP 28/56 bit- 48 kHz

Limiter Peak, RMS, Thermal

Controls Volume, Audio Input Sensitivity, DSP Preset

### Input

Main Connection VDE

Signal Input Balanced 1x Combo IN (MIC/LINE)

SIGNAL Out (Balanced) 1x XLR OUT (LINK)

### Mechanics

Housing Polypropylene

Grille Full Metal Grille

Handles 3 (2 on side 1 on top)

Pole Mount 36 mm

Width 350 mm (13.77 in)

Height 645 mm (25.40 in)

Depth 330 mm (12.99 in)

Weight 13.9 kg (30.46 lbs)

Angles Up Double wedge angle 45°