

Warm Audio WA-87 R2 Specs

Microphone

Form Factor	Stand/Boom Mount
-------------	------------------

Sound Field	Mono
-------------	------

Capsule	Condenser
---------	-----------

Polar Pattern	Cardioid, Figure-8, Omnidirectional
---------------	-------------------------------------

Pattern Selection	Switched
-------------------	----------

Circuitry	Solid-State
-----------	-------------

Pad	-10 dB
-----	--------

High-Pass Filter	80 Hz
------------------	-------

Tone Adjustment	<i>None</i>
-----------------	-------------

Indicators	<i>None</i>
------------	-------------

On-Board Controls	<i>None</i>
-------------------	-------------

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	125 dB SPL
-------------	------------

Equivalent Noise Level	-117 dB
------------------------	---------

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin
----------------------------	----------------------

Power

Operating Voltage	48 V (Phantom Power)
-------------------	----------------------

Physical

Color	Black
-------	-------

Mounting	Mic Clip, Shockmount (Included)
----------	---------------------------------

Construction Material	Brass
-----------------------	-------

Weight	5.51 lb / 2.5 kg
--------	------------------

Packaging Info

Package Weight

6.52 lb
