

Warm Audio WA-84 Specs

Microphone

Form Factor	Stand/Boom Mount
-------------	------------------

Sound Field	Mono
-------------	------

Operating Principle	Pressure Gradient Pressure Operated
---------------------	--

Capsule	Condenser
---------	-----------

Polar Pattern	Cardioid, Omnidirectional
---------------	---------------------------

Orientation	End Address
-------------	-------------

Circuitry	Solid-State
-----------	-------------

Pad	-10 dB
-----	--------

High-Pass Filter	<i>None</i>
------------------	-------------

Tone Adjustment	<i>None</i>
-----------------	-------------

Gain Adjustment	<i>None</i>
-----------------	-------------

Indicators	<i>None</i>
------------	-------------

On-Board Controls

Pad

Windscreen

Foam (Included)

Performance

Frequency Range

20 Hz to 20 kHz

Maximum SPL

123 dB SPL Peak (1 kHz)
133 dB SPL Peak (1 kHz, with Pad)

Impedance

200 Ohms

Load Impedance

1 Kilohms

Sensitivity

-39 dB at 1 kHz

Dynamic Range

107 dB A-Weighted

Signal-to-Noise Ratio

78 dB A-Weighted

Equivalent Noise Level

16 dB A-Weighted

Connectivity

Output Connectors (Analog)

1 x XLR 3-Pin Male (Locking, on Mic)

Headphone Connector

None

Power

Bus Power *None*

Operating Voltage 48 V (Phantom Power)

Physical

Color Nickel

Mounting Shockmount (Included)

Construction Material Metal

Dimensions \varnothing : 0.87 x L: 5.2" / \varnothing : 22 x L: 132 mm

Weight 4.3 oz / 122 g

Packaging Info

Package Weight 4.11 lb
