Overview

3usiness-class presentation features

Enjoy crisp, clear views of your documents and e-mail with 1366 x 768 resolution, 5M:1 dynamic contrast atio, and 5 ms response time on an 18.5-inch diagonal screen.[1] Quickly and easily connect to your levices with a VGA input.



Create an efficient, smart setup

Attach your HP Desktop Mini, HP Chromebox, or select HP Thin Client directly behind the display for an antegrated, affordable workspace that's perfect for small spaces. Or, use the integrated VESA mount to place the display on a wall or stand.[2]



Designed with the environment in mind

Reduce power consumption and help lower your costs with an intelligent, energy-efficient design that is ENERGY STAR® certified and EPEAT® Silver registered.[3] The display also includes mercury-free display acklights and arsenic-free display glass.

3et comfortable

Sustomize your display's position with adjustable tilt settings and viewing angles.

Norld-class support

Rest assured that your IT investment is supported by a three-year standard limited warranty. To extend you rotection, select optional HP Care Packs.[4]

Technical Specification

• 46.99 cm (18.5") Aspect ratio • 16:9 Native resolution • HD (1366 x 768 @ 60 Hz) Resolutions supported • 1366 x 768; 1280 x 1024; 1280 x 800; 1280 x 720; 1024 x 768; 800 x 600; 720 x 400; 640 x 480 Pixel pitch • 0.3 mm Brightness • 200 cd/m² [1] Contrast ratio • 600:1 static; 5000000:1 dynamic [1] Response time • [1] Onscreen controls Menu; Minus ("-"); Plus ("+"); OK; Power Display features Anti-glare; Plug and Play; User programmable; Language selection; On-screen controls; LED **Backlights** Physical security Security lock-ready (lock is sold separately) Input connector • 1 VGA Weight

• 2.6 kg

Weight note (metric)

With stand

Minimum dimensions (W x D x H)

• 44.14 x 4.54 x 27.77 cm

Dimensions (W x D x H) Note

Without stand

Dimensions With Stand (W x D x H)

• 44.14 x 21.81 x 33.86 cm

Power

• Input voltage: 100 to 240 VAC

Power consumption

• 17 W (maximum), 15 W (typical), 0.5 W (standby)

Operating humidity range

• 20 to 80% RH

Environmental

• Mercury-free display backlights; Arsenic-free display glass

Certifications and compliances

• CE; CB; KC; KCC; NOM; PSB; ICES; TUV-S; CCC; CEL; CECP; SEPA; EPA; ISC; VCCI; FCC; ETL; TUV-GS; TUV; VCCI; Taiwan BSMI; SmartWay Transport Partnership – NA only