

Xerox C405/DN Specs

Functions

Print
Scan
Copy
Fax

Printer

Printing Technology

Laser

Maximum Resolution

600 x 600 dpi

Print Speed

Simplex: 36 ppm
Duplex: 24 ppm

First Print Out Speed

Color: 13 seconds
Black: 12 seconds

Duplex Printing

Yes

Ink Palette

Black
Cyan
Magenta
Yellow

Ink Cartridge Configuration

4 individual cartridges

Duty Cycle

Monthly: 80,000 pages
Recommended Monthly Volume: 5,000 pages

Printer Language	PCL 5e PCL 6 PDF XPS TIFF JPEG HP-GL Adobe PostScript 3
------------------	--

Scanner

Type	Flatbed ADF
Image Sensor	Contact Image Sensor (CIS)
Optical Resolution	600 x 600 dpi
Scan Speed	Black & White: 40 ipm (Simplex), 52 ipm (Duplex) Color: 21 ipm (Simplex), 27 ipm (Duplex)
Color Depth	24-bit
Grayscale Depth	8-bit
Duplex Scanning	Yes
Maximum Scan Size	Flatbed: 8.5 x 11.7" / 21.6 x 29.7 cm ADF: 8.5 x 14" / 21.6 x 35.6 cm
Scan File Format	JPG TIFF XPS

PDF (searchable and password-protected)
PDF/A

Scanner Drivers
WIA
TWAIN

Copier

Copy Resolution
600 x 600 dpi

Copy Speed
Simplex: 36 cpm
Duplex: 24 cpm

First Copy-Out Time
Color: 11 seconds
Black: 8 seconds

Number of Copies
Up to 999

Reduction/Enlargement
25-400%

Duplex Copying
Yes

Maximum Copy Size
Flatbed: 8.5 x 11.7" / 21.6 x 29.7 cm
ADF: 8.5 x 14" / 21.6 x 35.6 cm

Fax

Modem Speed
33.6 kbps

Compression
MH
MR

MMR
JBIG

Fax Resolution 600 x 600 dpi

Memory 4 MB

Media Handling

Paper Handling
Input Tray 1
Bypass Tray
Automatic Document Feeder
Output Tray

Paper Sizes
Input Tray 1: 5.8 x 8.3" to 8.5 x 14" / 14.8 x 21 cm to 21.6 x 35.6 cm
Bypass Tray: 3 x 5" to 8.5 x 14" / 7.6 x 12.7 cm to 21.6 x 35.6 cm
ADF: 5.5 x 5.5" to 8.5 x 14" / 14 x 14 cm to 21.6 x 35.6 cm

Paper Weight
Input Tray 1: 16 lb bond to 80 lb cover / 60 to 220 gsm
Bypass Tray: 16 lb bond to 80 lb cover / 60 to 220 gsm
ADF: 16 lb bond to 45 lb cover / 60 to 125 gsm

Paper Capacity
Input Tray 1: 550 sheets
Bypass Tray: 150 sheets
ADF: 50 sheets
Output Tray: 250 sheets

Connectivity

Interface	USB 3.0 Ethernet NFC
Direct Printing	USB port
Processor	1.05 GHz Dual Core
Memory	2 GB
Compatible Operating Systems	Windows Mac OS X, macOS Linux

Physical

Control Panel	5" / 12.7 cm touchscreen LCD
Warm-Up Time	6 seconds
Acoustic Noise	Pressure Emissions: Power Emissions:
Power Requirements	110-127 VAC, 50/60 Hz, 10 A
Power Consumption	Maximum: 750 W Ready: 82 W Sleep: 4 W
Operating Conditions	Temperature: 50 to 90°F / 10 to 32°C Humidity: 10 to 85%
Storage Conditions	Temperature: 32 to 95°F / 0 to 35°C

Humidity: 10 to 85%

Dimensions (WxDxH)

17 x 21.3 x 23.6" / 43.2 x 54 x 59.9 cm

Weight

72 lb / 33 kg

Packaging Info

Package Weight

85.5 lb

Box Dimensions (LxWxH)

30 x 26.3 x 23.6"
