

Xerox 6515/DNI Specs

Functions

Print
Scan
Copy
Fax

Printer

Printing Technology

Laser

Maximum Resolution

1200 x 2400 dpi

Print Speed

Simplex: 30 ppm
Duplex: 18 ppm

First Print Out Speed

12 seconds

Maximum Print Size

8.5 x 14" / 21.6 x 35.6 cm

Duplex Printing

Yes

Duty Cycle

Monthly: 50,000 Pages
Recommended Monthly Volume: 3,000 Pages

Print Languages

Adobe PostScript 3
PCL 5e
PCL 6
PDF
TIFF

Scanner

Scanner Type	Flatbed ADF
Optical Resolution	600 x 600 dpi
Scan Speed	Black & White: 37 ipm Color: 21 ipm
Maximum Scan Area	Flatbed: 8.5 x 11.7" / 21.6 x 29.7 cm ADF: 8.5 x 14" / 21.6 x 35.6 cm
Color Depth	Color: 24-bit Grayscale: 8-bit
Scanner Drivers	WIA TWAIN
Scan File Format	JPG TIFF PDF Searchable PDF

Copier

Maximum Resolution	600 x 600 dpi
Copy Speed	Black & White, Simplex: 25 cpm Color, Simplex: 12 cpm Black & White, Duplex: 37 cpm Color, Duplex: 21 cpm

First Copy-Out Time	12 seconds
Maximum Copy Size	Flatbed: 8.5 x 11.7" / 21.6 x 29.7 cm ADF: 8.5 x 14" / 21.6 x 35.6 cm
Duplex Copying	Yes
Quantity	Up to 999 copies
Reduction / Enlargement	25-400%

Fax

Modem Speed	33.6 kbps
Fax Resolution	400 x 400 dpi
Compression	MH MR MMR JBIG
Fax Memory	4 MB
Speed Dial Locations	200 locations
Fax Broadcasting	200 destinations

Media Handling

Paper Handling	Input Tray 1 Bypass Tray Automatic Document Feeder Output Tray
Paper Sizes	Input Tray 1: 3 x 5.8" to 8.5 x 14" / 7.6 x 14.7 cm to 21.6 x 35.6 cm Bypass Tray: 3 x 5" to 8.5 x 14" / 7.6 x 12.7 cm to 21.6 x 35.6 cm ADF: 5.5 x 5.5" to 8.5 x 14" / 14 x 14 cm to 21.6 x 35.6 cm
Media Weight	Input Tray 1: 16 lb bond to 65 lb cover / 60 to 176 gsm Bypass Tray: 16 lb bond to 58 lb cover / 60 to 157 gsm ADF: 16 lb bond to 45 lb cover / 60 to 125 gsm
Paper Capacity	Input Tray 1: 250 Sheets Bypass Tray: 50 Sheets ADF: 50 Sheets Output Tray: 150 Sheets

Connectivity

Interfaces	USB 3.0 Ethernet Wi-Fi
Direct Printing	USB Port Wi-Fi Direct
OS Compatibility	Windows Mac OS X, macOS Linux

Processor	1.05 GHz
Memory	2 GB
Fonts	PostScript: 136 Fonts PCL: 88 Fonts

General Attributes

Control Panel	Color Touchscreen
Warm-Up Time	27 Seconds
Power Requirements	120 VAC ($\pm 10\%$), 60 Hz (± 3 Hz), 12 A
Power Consumption	Maximum: 350 W Ready: 51 W Sleep: 1.1 W Off: 0.2 W
Acoustic Noise	Sound Power Operating: 6.8 B(A) Standby: 4.3 B(A) Sound Pressure Operating: 52.5 dB(A) Standby: 26.3 dB(A)
Operating Conditions	Temperature: 41 to 90°F / 5 to 32°C Humidity: 15-85%
Storage Conditions	Temperature: -4 to 104°F / -20 to 40°C Humidity: 15-85%

Certifications	FCC Part 15 Class A; FCC Part 68; CE Mark applicable to Directives 2006/95/EC, 2004/108/EC and 1999/5/EC UL 60950-1/CSA 60950-1-07, 2nd Edition; NOM; GS Mark; EAC; Citrix certified; Cerner (undergoing evaluation); Apple AirPrint certification; Google Cloud Print certification; Mopria certified; Wi-Fi Alliance certified; Blue Angel; MEDITECH; ENERGY STAR; ECOLOGO; EPEAT (United States)
----------------	---

Dimensions (WxHxD)	16.5 x 19.7 x 19.9" / 42 x 50 x 50.6 cm
--------------------	---

Weight	67.7 lb / 30.7 kg
--------	-------------------

Packaging Info

Package Weight	78.5 lb
----------------	---------

Box Dimensions (LxWxH)	26.2 x 25 x 22.8"
------------------------	-------------------
