

Model Configuration

Model	C8000/DT
Standard functions	Cloud, Print
Recommended monthly print volume	Up to 20,000 pages
Duty cycle	Up to 205,000 images/month [Ⓢ]
Two-sided output	Standard
First-page-out time, printing	As fast as 11 seconds color / 11 seconds black and white
Print speed	Color: up to 45 ppm Black: up to 45 ppm
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, NFC Tap-to-Pair, Wi-Fi and Wi-Fi Direct (optional)
Connectivity (optional)	Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported)
Warranty	One-year on-site
Price	\$2,699.00 [Ⓢ]
	<div data-bbox="846 1671 1089 1745" style="border: 1px solid red; padding: 5px; text-align: center; margin: 10px auto; width: fit-content;">ADD TO CART</div> <div data-bbox="802 1791 1135 1864" style="border: 1px solid black; padding: 5px; text-align: center; margin: 10px auto; width: fit-content;">OTHER WAYS TO BUY</div>

Print

Processor	Dual-core 1.6 GHz
Print memory (standard/max)	4 GB / 4 GB
Hard drive	320 GB HDD (optional)
OS support	Citrix®, Fedora Core, HP-UX®, IBM® AIX®, Oracle® Solaris, Redhat® Enterprise Linux®, SAP®, SUSE®, Windows Server 2008 SP2, Server 2008 R2 SP1, Server 2012, Server 2012 R2, Server 2016, Windows® 7, 8, 8.1, 10, macOS® 10.12, 10.13, 10.14
Page Description Languages (PDL)	Adobe® PostScript® 3™, HP-GL, JPEG, PCL® 5e, 6, PDF, TIFF, XPS
PostScript® fonts	136
PCL® fonts	83
Mobile printing	@PrintByXerox App, Apple® AirPrint®, Google Cloud Print™, Xerox® Global Print Driver®, Xerox® Mobile Express Driver®, Xerox® Print Service Plug-in for Android™, Xerox® Pull Print Driver
Mobile printing (optional)	Xerox® Workplace Cloud, Xerox® Workplace Suite

Media Handling

Standard paper capacity	1,140 sheets
Maximum paper capacity	5,140 sheets
Output	500 sheets

capacity	
Paper capacity	Tray (Bypass tray): 100 sheets Tray 1: 520 sheets Tray 2: 520 sheets
Paper size	Tray (Bypass tray): Custom sizes: 3.5 x 3.87 in. to 11.7 x 17 in. (88.9 x 98.4 mm to 320 x 482.6 mm) Tray 1: Custom sizes: 3.9 x 5.8 in. to 11.7 x 17 in. (139.7 x 182 mm to 297 x 432 mm) Tray 2: Custom sizes: 3.9 x 5.8 in. to 12x 18 in. (139.7 x 182 mm to 297 x 432 mm)
Optional High Capacity Feeder	High-capacity tandem tray: 2,000 sheets Two tray module: 1,140 sheets High-capacity feeder: 2,000 sheets

Security

Security features	AES 256-bit Encryption, Access Controls, Audit Log, Certificate Path Validation, Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP), Cisco Identity Services Engine (ISE) Integration, Detection of external program falsification (XCP Plug-in), Domain Filtering, FIPS 140-2, Firmware Verification, IP Address Filtering, IPsec, Immediate Disk Overwrite (requires HDD/Productivity Kit), Network Authentication, Port Filtering, Pre-installed Self-Signed Certificates, Role Based Permissions, SNMPv3, Secure Print, Security Certificate Management, Smart Card Enablement (CAC/PIV/.NET), Status Protocol (OCSP), TLS/SSL
--------------------------	---

Electrical

Power consumption	Operating: 2,300 W Standby: 75.3 W Power save: as low as 0.67 W
ENERGY STAR	ENERGY STAR® qualified

Operating Environment

Temperature (operating)	50 - 83 ° F (10 - 28 ° C)
Relative humidity (operating)	15 - 85 % RH (noncondensing)
Warm-up time (from power save mode)	9.6 seconds

Dimensions

Dimensions (WxDxH)	24.4 x 28.5 x 31.9 in. (620 x 723 x 809.3 mm)
Weight	178 lb (80.8 kg)

Certifications

Certifications	Apple® AirPrint®, Blue Angel, Bonjour, Cerner, ECOLOGO®, EPEAT®, FIPS 140-2, IPv6 Ready, MEDITECH, Mopria®, SAP, WHQL, Wi-Fi Direct
Sustainability	<u>EPEAT</u> <u>ENERGY STAR®</u>