

Model Configuration

Model	C7000/DN
Standard functions	Print
Recommended monthly print volume	Up to 10,000 pages
Duty cycle	Up to 153,000 images/month [Ⓢ]
Two-sided output	Standard
First-page-out time, printing	As fast as 7.6 seconds color / 5.1 seconds black and white
Print speed	Color: up to 35 ppm Black: up to 35 ppm
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, NFC Tap-to-Pair
Connectivity (optional)	Wi-Fi 802.11n/g/b/a and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported)
Warranty	One-year on-site
Price	\$1,659.00 [Ⓢ]
	<div data-bbox="846 1640 1089 1711" style="border: 1px solid red; padding: 5px; text-align: center; margin: 10px auto; width: fit-content;">ADD TO CART</div> <div data-bbox="802 1757 1135 1829" style="border: 1px solid black; padding: 5px; text-align: center; margin: 10px auto; width: fit-content;">OTHER WAYS TO BUY</div>

Print

Processor	Dual-core 1.05 GHz
Print memory (standard/max)	2 GB / 2 GB
OS support	Citrix, Fedora Core 24, HP-UX® 11iv3, IBM® AIX® 7.2, Linux, Mac OS® X 10.10, 10.11, & 10.12, Oracle® Solaris 11.3, Redhat Enterprise, SUSE® 13.2, Windows® 10, Windows® 2003 Server, Windows® 2008 Server, Windows® 7, Windows® 8, Windows® Server 2012, Xerox Global Printer Driver, Xerox Mobile Express Driver
Page Description Languages (PDL)	Adobe® PostScript® 3™, HP-GL, JPEG, PCL® 5e, 6, PDF, TIFF, XPS
PostScript® fonts	136
PCL® fonts	83
Mobile printing	@PrintByXerox App, Apple AirPrint, Google Cloud Print™, Mopria® Certified, Mopria® Print Service Plug-in for Android, Xerox® Print Service Plug-in for Android
Mobile printing (optional)	Xerox® Print Management and Mobility Service, Xerox® Print Management and Mobility Suite

Media Handling

Standard paper capacity	620 sheets
Maximum paper capacity	2,180 sheets
Output capacity	500 sheets
Paper	Tray (Bypass tray): 100 sheets

capacity	<p>Tray 1: 520 sheets</p> <p>Tray 2 (optional): 520 sheets</p> <p>Tray 3 (optional): 520 sheets</p> <p>Tray 4 (optional): 520 sheets</p>
Paper size	<p>Tray (Bypass tray): Custom sizes: 3.5 x 3.87 in. to 11.7 x 17 in. (88.9 x 98.4 mm to 297 x 432 mm)</p> <p>Tray 1: Custom sizes: 5.5 x 7.1 in. to 11.7 x 17 in. (139.7 x 182 mm to 297 x 432 mm)</p> <p>Tray 2 (optional): Custom sizes: 5.5 x 7.1 in. to 11.7 x 17 in. (139.7 x 182 mm to 297 x 432 mm)</p> <p>Tray 3 (optional): Custom sizes: 5.5 x 7.1 in. to 11.7 x 17 in. (139.7 x 182 mm to 297 x 432 mm)</p> <p>Tray 4 (optional): Custom sizes: 5.5 x 7.1 in. to 11.7 x 17 in. (139.7 x 182 mm to 297 x 432 mm)</p>

Security

Security features	<p>AES 256-bit Encryption, Access Controls, Audit Log, Automatic Self-Signed Certificate Creation, Certificate Path Validation, Certificate Revocation List (CRL)/Online Certificate Status Protocol (OCSP), Detection of external program falsification (XCP Plug-in), Domain Filtering, FIPS 140-2, Firmware Verification, IP Address Filtering, Immediate Disk Overwrite (requires optional HDD), Network Authentication, Port Filtering, Role Based Permissions, SNMPv3, Secure Print, Security Certificate Management, Smart Card Enablement (CAC/PIV/.NET), TLS/SSL</p>
--------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Electrical

Power consumption	<p>Operating: 1,600 W</p> <p>Standby: 94 W</p> <p>Power save: as low as 0.61 W</p>
ENERGY STAR	<p>ENERGY STAR® qualified (DN configuration only)</p>

Operating Environment

Temperature (operating)	50 - 90 ° F (10 - 32 ° C)
Relative humidity (operating)	10 - 85 % RH (noncondensing)
Warm-up time (from power save mode)	12 seconds

Dimensions

Dimensions (WxDxH)	23.23 x 26.41 x 25.08 in. (590 x 670.8 x 637 mm)
Weight	119.71 lb (54.3 kg)

Certifications

Certifications	Apple® AirPrint®, Blue Angel, Bonjour, Cerner, ECOLOGO®, EPEAT®, FIPS 140-2, IPv6 Ready, MEDITECH, Mopria®, SAP, WHQL, Wi-Fi Direct
Sustainability	<u>EPEAT</u> <u>ENERGY STAR®</u>