Model Configuration

Model	B405/DN
Print speed	up to 47 ppm
Recommended monthly print volume	Up to 15,000 pages
Duty cycle	Up to 150,000 images/month ^①
Processor speed	1.05 GHz
Print memory (standard)	2 GB standard
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 3.0, NFC Tap-to-Pair (optional: Wi-Fi 802.11n and Wi-Fi Direct with optional Wi-Fi Kit (concurrent wired and wireless connections supported))
Two-sided output	Standard
Warranty	One-year on-site
Price	\$799 ^①
	ADD TO CART OTHER WAYS TO BUY

Copy

copy resolution	
First- page-out time, copying	As fast as 6.2 seconds
Copy features	Automatic Background Suppression, Book Copying with Center Erase, Collation, Darkness Control, Edge Erase, ID Card Copy, Image Shift, N-up, Original Type, Reduce / Enlarge 25% to 400%, Sample Copy, Sharpness

Print

Maximum print resolution	1200 x 1200 dpi
First-page- out time, printing	As fast as 5.1 seconds
Page Description Languages (PDL)	Adobe® PostScript® 3™, HP-GL, JPEG, PCL® 5e, 6, PDF, TIFF, XPS
Print features	Application defaults, Bi-directional real-time status, Booklet creation, Draft mode, Job Monitoring, Job identification, Personal print, Print from USB, Sample set, Saved job, Scaling, Secure Print, Skip blank pages, Store and Recall driver settings, Two-sided Printing (default), Xerox® Earth Smart Driver Settings
Mobile printing	<u>Apple® AirPrint™</u> , <u>Google Cloud Print™</u> , <u>Mopria®</u> , <u>Xerox® Print Service Plug-in for Android™</u> (optional: <u>Xerox® Mobile Print Cloud, Xerox® Mobile Print Solution</u> , @PrintByXerox, WiFi Direct®[with optional Wi-Fi Kit])

Scan

Scan	
destinations	

Scan to Home, Scan to Network (FTP or Browse SMB), Scan to USB, Scan to email

Fax

Fax features	Direct Fax, Fax Forward to Email, Fax dialing via Unified Address Book (up to 2,000 contacts), LAN Fax, Walk-up Fax* * - Analog phone line required.
Fax compression	MH, MR, MMR, JBIG

Print Drivers

os
support

HP UX® 11, HP UX® 11i, IBM AIX® 5, Mac OS® X 10.5 and later, Redhat Enterprise 4 and 5, Solaris 10, Solaris 9, Ubuntu®, Windows® 2003 Server, Windows® 2008 Server, Windows® 7, Windows® Vista, Windows® XP, Xerox Global Printer Driver, Xerox Mobile Express Driver

Font capabilities

PostScript®fonts	144
PCL® fonts	82

Media Handling

Output capacity	250 sheets
Document handler	Reversing Automatic Document Feeder (RADF) Capacity: 60 sheets

	Size: 5.5 x 5.5 in. to 8.5 x 14 in.
	(139.7 x 139.7 mm to 216 x 356 mm)
Paper capacity	Tray (Multipurpose tray): 150 sheets Tray 1: 550 sheets Tray 2 (optional): 550 sheets Tray 3 (optional): 550 sheets Tray 4 (optional): 550 sheets
Paper size	Tray (Multipurpose tray): Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76.2 x 127 mm to 216 x 356 mm) Tray 1: Custom sizes: 3 x 5 in. to 8.5 x 14 in. (76.2 x 127 mm to 216 x 356 mm) Tray 2 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm) Tray 3 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm) Tray 4 (optional): Custom sizes: 5.5 x 8.3 in. to 8.5 x 14 in. (139.7 x 210 mm to 216 x 356 mm)

Security

		256-bit Encryption, Access controls, Audit log, Automatic Self-Signed Certificate
۱.	Security	Creation, Certificate Path Validation, Certificate Revocation Settings, Domain Filtering,
	features	FIPS 140-2, Firmware Verification, IP Address Filtering, Network authentication, Port
	reatures	Filtering, Role based permissions, SNMPv3, Secure Email, Secure Fax, Secure Print,
		Secure Scan, Security certificates, Smart Card Enablement Kit (CAC/PIV/.NET), TLS

Electrical

Power consumption	Operating: 620 W Standby: 60 W Power save: as low as 0.83 W
ENERGY STAR	ENERGY STAR® qualified

Operating Environment

Temperature (operating)	50 - 90 ° F (10 - 32 ° C)
Relative humidity 10 - 8 (operating)	10 - 85 % RH (noncondensing)

Dimensions

Dimensions (WxDxH)	19.5 x 19.5 x 21.7 in. (495 x 495 x 551 mm)
Weight	48 lb (22 kg)

Certifications

Sustainability	EPEAT	
	ENERGY STAR®	