

Specifications

SKU

SKU	J7Z99A
------------	---------------

PRINT

Print speed, black	41 - 50
---------------------------	----------------

Color or black	Color
-----------------------	--------------

Print speed, color	41 - 50
---------------------------	----------------

CATEGORY

Product type	Laser printers
---------------------	-----------------------

Family brand	LaserJet
---------------------	-----------------

USAGE

Perfect for	Enterprise
--------------------	-------------------

FEATURES

Functions	Print only
------------------	-------------------

Features	Two-sided printing
-----------------	---------------------------

CONNECTIVITY AND COMMUNICATIONS

Connectivity, optional	HP Jetdirect 2900nw Print Server J8031A; HP Jetdirect 3000w NFC/Wireless Accessory J8030A
-------------------------------	--

Connectivity, standard	1 Hi-Speed USB 2.0 Device; 2 Hi-Speed USB 2.0 Host; 1 Gigabit/Fast Ethernet 10/100/1000 Base-TX network; Hardware Integration Pocket
-------------------------------	---

Network capabilities	Yes, via HP Jetdirect Ethernet embedded print server (standard) which supports: 10Base-T, 100Base-Tx, 1000Base-T; 802.3az (EEE) support on Fast Ethernet and Gig Links; IPsec (standard); 802.11a/b/g/n wireless networking (optional).
Wireless capability	Optional, enabled with purchase of HP Jetdirect 2900nw Print Server J8031A or HP Jetdirect 3000w NFC/Wireless Accessory J8030A
Mobile printing capability	HP ePrint; Apple AirPrint™; Mopria-certified
Network protocols supported	Via built-in networking solution: TCP/IP, IPv4, IPv6; Print: TCP-IP port 9100 Direct Mode, LPD (raw queue support only), Web Services Printing, IPP 2.0, Apple AirPrint™, HP ePrint, FTP Print, Google Cloud Print; Discovery: SLP, Bonjour, Web Services Discovery; IP Config: IPv4 (BootP, DHCP, AutoIP, Manual, TFTP Config, ARP-Ping), IPv6 (Stateless Link-Local and via Router, Statefull via DHCPv6); Management: SNMPv2/v3, HTTP/HTTPs, Telnet, TFTP Config, FTP FW Download, Syslog; Security: SNMPv3, SSL Cert Management, Firewall, ACL, 802.1x
PRINTING MEDIA HANDLING	
Finished output handling	Sheetfed
Output capacity	Up to 500 sheets
Maximum output capacity (sheets)	Up to 500 sheets
Standard output capacity (transparencies)	Up to 200 sheets
Media type and capacity, tray 1	Paper: 100 sheets of 75 gsm media; Envelopes: 10

Media type and capacity, tray 2	Plain media (75 g/m²) sheets: 550 (55 mm stack height); Glossy media sheets (120 g/m²): 250 (30 mm stack height)
--	---

Paper handling input, standard	100-sheet multi-purpose tray, 550-sheet input tray 2
---------------------------------------	---

Paper handling input, optional	Optional 1x550-sheet paper feeder, optional 1x550-sheet Paper Feeder with Stand and Cabinet, optional 3x550-sheet Paper Feeder with Stand, optional 1x550/2000-sheet HCI Feeder and Stand
---------------------------------------	--

Input capacity	Up to 650 sheets
-----------------------	-------------------------

Paper handling output, standard	500-sheet output bin
--	-----------------------------

Standard output capacity (envelopes)	Up to 85 envelopes
---	---------------------------

Maximum input capacity (sheets)	Up to 3200 sheets
--	--------------------------

Standard input capacity (envelopes)	Up to 10
--	-----------------

DISPLAY SPECIFICATIONS

Display	2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle)
----------------	---

Display area (metric)	54 x 40.5 mm
------------------------------	---------------------

ENVIRONMENTAL

Acoustic power note	Printing color simplex A4 at 48 ppm. Acoustic values are subject to change. For current information see http://www.hp.com/support.
Acoustic pressure emissions bystander (active, printing)	53 dB(A)
Non-Operating Humidity Range	10 to 90% RH
Operating humidity range	10 to 80% RH
Storage temperature range	-20 to 40°C
Operating temperature range	15 to 30°C
Acoustic power emissions	6.8 B(A)
Recommended operating temperature range	17.5 to 25°C
Acoustic power emissions (ready)	4.6 B(A)
Acoustic pressure emissions bystander (ready)	31 dB(A)

CARTRIDGES AND PRINTHEADS

Technology	Laser
-------------------	--------------

Number of print cartridges

4 (1 each black, cyan, magenta, yellow)

Replacement cartridges

HP 655A Black Original LaserJet Toner Cartridge (~12,500 yield) CF450A; HP 656X High Yield Black Original LaserJet Toner Cartridge (~27,000 yield) CF460X; HP 655A Cyan Original LaserJet Toner Cartridge (~10,500 yield) CF451A; HP 656X High Yield Cyan Original LaserJet Toner Cartridge (~22,000 yield) CF461X; HP 655A Yellow Original LaserJet Toner Cartridge (~10,500 yield) CF452A; HP 656X High Yield Yellow Original LaserJet Toner Cartridge (~22,000 yield) CF462X; HP 655A Magenta Original LaserJet Toner Cartridge (~10,500 yield) CF4533A; HP 656X High Yield Magenta Original LaserJet Toner Cartridge (~22,000 yield) CF463X

PRINT SPEED

Print speed black (normal, letter)

Up to 50 ppm

Print speed black (normal, A4)

Up to 47 ppm

Print speed colour (normal, A4)

Up to 47 ppm

Print speed color (normal, letter)

Up to 50 ppm

Print speed duplex (A4)

Up to 47 ppm

**Print speed
black
(Landscape,
A5)** **Up to 74 ppm**

**Print speed
black
(Portrait,
A5)** **Up to 4 ppm**

**Print speed
duplex
(letter)** **Up to 50 ppm**

**Print speed
duplex
(A4)** **Up to 47 ppm**

**Print speed
duplex
(letter)** **Up to 50 ppm**

**Print speed
color
(Portrait,
A5)** **Up to 4 ppm**

**Print speed
color
(Landscape,
A5)** **Up to 74 ppm**

BATTERY AND POWER

Power **Input voltage: 100V to 127V nominal (+/-10%), 50 - 60Hz nominal (+/- 3Hz), 12 A; Input voltage: 220V to 240V nominal, (+/-10%) 50 - 60Hz nominal (+/- 3Hz), 6 A**

Power Consumption Description **690 watts (printing), 31 watts (ready), 0.7 watts (sleep), 0.7 watts (Auto Off/Manual On), 0.1 (Manual Off)**

Power supply type **Built in 115V or 220V Power Supply (not dual voltage, power supply varies by part number with option code identifier)**

PRINT TIME

First page out black (letter, ready) **As fast as 6.4 sec**

First page out black (A4, ready) **As fast as 6.5 sec**

First page out color (A4, ready) **As fast as 6.5 sec**

First page out color (letter, ready) **As fast as 6.4 sec**

First page out black (letter, sleep) **As fast as 8.4 sec**

First page out black (A4, sleep) **As fast as 8.5 sec**

First page out color (letter, sleep) **As fast as 8.4 sec**

First page out color (A4, sleep) **As fast as 8.5 sec**

PRINTER SPECIFICATIONS

Duty cycle (monthly, letter)	Up to 100,000 pages
Duty cycle note	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs to satisfy the demands of connected individuals or groups.
Envelope feeder	No
Recommended monthly page volume note	HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
Functions	Print
Internal Storage	Optional, 500 GB (with accessory B5L29A)
Print languages	HP PCL 6; HP PCL 5c; HP postscript level 3 emulation, native PDF printing (v 1.7), URF (AirPrint)
Paper trays, maximum	Up to 5
Duty cycle (monthly, A4)	Up to 100,000 pages
Paper trays, standard	2
Recommended monthly page volume	2000 to 14,000
Print technology	Laser

Duplex printing **Automatic (standard)**

Fonts and typefaces **105 internal TrueType fonts scalable in HP PCL, 92 internal scalable fonts in HP Postscript level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale Mono WorldType); 2 Internal Windows Vista 8 Fonts (Calibri, Cambria); additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IPDS Emulation available at <http://www.hp.com/go/laserjetfonts>**

Automatic paper sensor **Yes**

Printer management **HP JetAdvantage Security Manager; HP SNMP Proxy Agent; HP Web JetAdmin Software; HP WS Pro Proxy Agent; Printer Administrator Resource Kit for HP Universal Print Driver**

Print colours **Yes**

Target user and print volume **For teams over 25 users; Prints up to 14,000 pages/month**

CERTIFICATION AND COMPLIANCE

ENERGY STAR® certified **Yes**

Energy Efficiency Compliance **ENERGY STAR® qualified; EPEAT® Silver; EPEAT® Gold (#AAZ; #201 options only); CECP**

Electromagnetic Emission Standard **CISPR 22:2008 (International) - Class A, CISPR 32:2012 (International) - Class A, EN 55032: 2012 (EU) - Class A, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 55024: 2010, EMC Directive 2014/30/EU, FCC CFR 47 Part 15 Class A / ICES-003, Issue 6 Class A, Other EMC approvals as required by individual countries**

Safety Approvals and Requirements

EC 60950-1:2005 +A1:2009 +A2:2013 (International); EN60950-1:2006 +A11:2009 +A1:2010 +A12:2011 +A2:2013 (EU); EN 60825-1:2014 / IEC 60825-1:2014 (Class 1 Laser Product); EN 62479:2010 / IEC 62479:2010 Low Voltage Directive 2014/35/EU with CE Mark (Europe); GS Certificate (Germany, Europe); UL/cUL Listed and UC CoC (US/Canada); CAN/CSA C22.2 No. 60950-1-07 Amendment 2:2014; Other safety approvals as required by individual countries

Environmental **Mercury free**

FCC Class A Emissions **FCC Class A emissions - for use in commercial environments, not residential environments**

GEOGRAPHIC

Country of origin **Made in Japan (All options except AB2); Product of Japan, Assembled in China (Option AB2)**

WARRANTY

Warranty **1 year onsite limited warranty**

MEMORY

Memory slots **1 slot, 144-pin, DDR3 DIMM**

Memory upgrade **Expandable to 3 GB through one 144-pin DDR3 DIMM slot**

Memory **1 GB**

Memory, maximum **3 GB**

DIMENSIONS

Dimensions without stand (W x D x H) **510 x 458 x 482 mm**

Package dimensions (W x D x H) **653 x 596 x 578 mm**

Maximum dimensions (W x D x H)	963 x 770 x 482 mm
---------------------------------------	---------------------------

WEIGHTS

Weight	31.2 kg
---------------	----------------

Package weight	35.9 kg
-----------------------	----------------

SYSTEM COMPONENTS

Control panel	2.7-in (6.86 cm) QVGA LCD (color graphics) rotating (adjustable angle) display with 24-key pad
----------------------	---

PROCESSOR

Processor speed	1.2 GHz
------------------------	----------------

BOX CONTENTS

Cable included	No, please purchase (USB) cable separately
-----------------------	---

SUPPORTED PRINTING MEDIA

Media sizes supported	Tray 1: A4, A5, A6, RA4, B5, B6, 16k, 10 x 15 cm, Oficio, postcards (JIS single and double) envelopes (DL, C5, B5, C6); Tray 2: A4, A5, A6, RA4, B5, B6, 10 x 15 cm, Oficio, 16k, Dpostcard; Optional 550-sheet trays 3, 4, 5: A4, A5, A6, RA4, B5, B6, 10 x 15 cm, Oficio, 16k, Dpostcard; Optional 2,000-sheet high-capacity Tray 4: A4
------------------------------	--

Media size, tray 3	1x550 feeders: A4, A5, A6, RA4, B5, B6, 10 x 15 cm, Oficio, 16k, Dpostcard, envelopes (DL, C5, B5, C6); 101.6 x 148 to 216 x 356 mm; 2000-sheet high-capacity feeder: A4
---------------------------	---

Media size, tray 1	A4, A5, A6, RA4, B5, B6, 16k, 10x15cm, Oficio, postcards (JIS single and double) envelopes (DL, C5, B5, C6); 76 x 127 to 216 x 356 mm
---------------------------	--

Media size, tray 2	A4, A5, A6, RA4, B5, B6, 10x15cm, Oficio, 16k, Dpostcard, envelopes (DL, C5, B5, C6); 101.6 x 148 to 216 x 356 mm
---------------------------	--

Standard media sizes (duplex) A4; A5; RA4; B5; Oficio; 16k

Media weight, supported Tray 1: 60-220 g/m² (plain), 120 to 220 g/m² (glossy); Tray 2 and automatic two-sided printing unit: 60 to 163 g/m² (plain), 120 to 220 g/m² (glossy); Optional Trays 3, 4, 5 1x550-sheet feeders: 60 to 163 g/m² (plain), 120 to 220 g/m² (glossy); Optional Tray 4 2,000 high capacity input: 60-163 g/m² (plain)

Media types Paper (plain, light, bond, recycled, mid-weight, heavy, mid-weight glossy, heavy glossy, extra heavy, extra heavy glossy, cardstock, card glossy), color transparency, labels, letterhead, envelope, preprinted, prepunched, colored, rough, opaque film, user-defined

Media weight (tray 2) 60 to 163 g/m² (plain); 120 to 220 g/m² (glossy)

Recommended media weight (duplex) 60 to 163 g/m² (plain); 120 to 220 g/m² (glossy)

Media weight (tray 1) 60-220 g/m² (plain), 120 to 220 g/m² (glossy)

Media weight (tray 3) 1x550 feeders: 60 to 163 g/m² (plain), 120 to 220 g/m² (glossy); 2,000-sheet high capacity input tray 4: 60 to 163 g/m² (plain)

Media sizes, custom Tray 1: 76 x 127 to 216 x 356 mm; Tray 2: 101.6 x 148 to 216 x 356 mm; Optional 550-sheet trays: 101.6 x 148 to 216 x 356 mm; Optional 2,000-sheet high-capacity tray: custom sizes not supported in this tray

SYSTEM REQUIREMENTS

Minimum System Requirements for Macintosh 1.3 GB available hard drive space; Internet; OS hardware requirements see Apple.com for more info

Minimum System Requirements 2GB available hard disk space, OS hardware requirements see microsoft.com

SOFTWARE AND APPLICATIONS

Driver updates

Current HP printer drivers and software can be obtained from the HP Customer Care Web site: In the US, go to www.hp.com/support/colorljM652; Outside the US, go to <http://www.hp.com/support> 1. Go to <http://www.hp.com/support>. Select the country/region. 2. Select Drivers & Downloads 3. Enter a product name/number. 4. Under Download Options, select Drivers, Software & Firmware 5. Select the operating system version. 6. Then select DOWNLOAD.

Downloadable software

HP Easy Start (Guided Software Install for Windows OS and Mac); HP ePrint Software (ePrint Mobile Driver for Windows); HP ePrint Software (for Windows); HP Imaging & Printing Security Center; HP JetAdvantage Security Manager; HP Mobile Printing
<http://www8.hp.com/us/en/ads/mobility/overview.html>; HP PCL6 (XPS) print driver only (No installer for "Add Printer" installs); HP PCL6 (XPS) print driver with installer; Product Documentation and Support; HP Proxy Agent Software; HP Universal Print Drivers (PCL6 & PS for Windows); Linux/Unix Print Drivers; Mac Software Solution; Printer Administrator Resource Kit; SAP (PS Print Drivers); Web JetAdmin; Windows driver only solution; Windows Full Software Solution

Mac compatible

Yes

Software included

HP Connected, HP Device Experience (DXP), HP PCL 6 (XPS) Printer Driver, HP Software Installer/Uninstaller, Mac OS Welcome Screen (Directs users to 123.HP.com or OS App Source for printer software), Online user manuals

SUPPORTED OPERATING SYSTEMS

**Compatible
Operating
Systems**

Android, Linux Boss (5.0), Linux Debian (7.0, 7.1, 7.2, 7.3, 7.4, 7.5, 7.6, 7.7, 7.8, 7.9, 8.0, 8.1, 8.2, 8.3, 8.4, 8.5, 8.6), Linux Fedora (22, 23, 24), Linux Mint (17, 17.1, 17.2, 17.3, 18), Linux Red Hat Enterprise (6.0, 7.0), Linux SUSE (13.2, 42.1), Linux Ubuntu (12.04, 14.04, 15.10, 16.04, 16.10), OS macOS 10.12 Sierra, OS X 10.10 Yosemite, OS X 10.11 El Capitan, UNIX, Windows 10 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows 7 all 32- & 64-bit editions, Windows 8/8.1 all 32- & 64-bit editions (excluding RT OS for Tablets), Windows Vista all 32bit editions (Home Basic, Premium, Professional, etc.), Windows XP SP3 32-bit editions (XP Home, XP Pro, etc.)

**Compatible
network
operating
systems**

Citrix MetaFrame Presentation Server 3.0, Citrix MetaFrame XP Presentation Server (Feature Release 1, 2, and 3), Citrix on Windows Server 2003/2003R2, Citrix on Windows Server 2008/2008R2/2008 R2 SP1, Citrix on Windows Server 2012/2012R2, Citrix Presentation Server 4.0/4.5, Citrix XenApp 5.0 (Plus Feature Pack 2 & 3) for Windows Server 2008 Terminal Services 32- and 64-bit, Citrix XenApp 6.0/6.5 [for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenApp 6.0/6.5/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenApp 7.5 [for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit], Citrix XenDesktop 5.6 [for Windows Server 2008 R2 Terminal Services, 32- and 64-bit], Citrix XenDesktop 5.6/7.0/7.5 [for Windows Server 2008 R2 SP1 Terminal Services, 32- and 64-bit], Citrix XenDesktop 7.0/7.5 [for Windows Server 2012 and 2012 R2 Terminal Services, 64-bit], Novell NetWare 6.5/SP8 Novell Clients www.novell.com/iprint, Novell iPrint Appliance v1.0, Novell Open Enterprise Server 11/SP1, Novell Open Enterprise Server 2 for Linux, Novell Servers www.novell.com/iprint), Windows Server 2003/2003 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2003/2003 R2 32-bit (SP1/SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 32-/64-bit (SP2) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008 R2 64-bit (SP1) Standard/Enterprise (+ Cluster & Terminal Services), Windows Server 2008/2008 R2 32-/64-bit (SP1/SP2) Standard/Enterprise/Datacenter (+ Cluster & Terminal Services), Windows Server 2012/2012 R2 64-bit Standard/Foundation/Essentials/Datacenter (+ Cluster & Terminal Services)

**Operating
system
(supported
note)**

Full solution software available only for Windows 7 and newer, UPD software available only for Windows 7 and newer HP Software for Mac and Windows is no longer included on the CD, but can be downloaded from 123.hp.com, Legacy Windows Operating Systems (XP, Vista, and equivalent servers) get print and Scan drivers only, with a reduced feature set Windows RT OS for Tablets (32- & 64-bit) uses a simplified HP print driver built into the RT OS

PRINT RESOLUTION

Print quality black (normal) Up to 600 x 600 dpi

Print quality black (best) Up to 1200 x 1200 dpi

Print quality color (best) Up to 1200 x 1200 dpi

Print resolution color (normal) Up to 600 x 600 dpi

Print resolution black (fine lines) Up to 1200 x 1200 dpi

Print resolution color (fine lines) Up to 1200 x 1200 dpi

RACK AND POWER SPECIFICATIONS

Typical electricity consumption (TEC) number 1.93 kWh/Week (Blue Angel); 0.563 kWh/Week (Energy Star 3.0)

Number of users 10-30 Users

Blue Angel (sleep mode) 0.70 Watts

PRINT AREA

**Right
margin
(A4)** **4.3 mm**

**Top
margin
(A4)** **4.3 mm**

**Bottom
margin
(A4)** **4.3 mm**

**Left
margin
(A4)** **4.3 mm**

SERVICES

**Services
(Care
Pack)**

**U9NZ6E - HP 3y Nbd+DMR CLJ Ent M65x HW
Supp; U9NZ7E - HP 4y Nbd+DMR CLJ Ent M65x
HW Supp; U9NZ8E - HP 5y Nbd+DMR CLJ Ent
M65x HW Supp; U9NZ9E - HP 3y 4h 9x5+DMR CLJ
Ent M65x HW Supp; U9PA0E - HP 4y 4h 9x5+DMR
CLJ Ent M65x HW Supp; U9PA1E - HP 5y 4h
9x5+DMR CLJ Ent M65x HW Supp; U9PA2E - HP
3y 4h 13x5+DMR CLJ Ent M65x HW Supp; U9PA4E
- HP 5y 4h 13x5+DMR CLJ Ent M65x HW Supp;
U9PA5E - HP 3y NBD CTR+DMR CLJ Ent M65x
HW Supp; U9PA6E - HP 4y NBD CTR+DMR CLJ
Ent M65x HW Supp; U9PA7E - HP 5y NBD
CTR+DMR CLJ Ent M65x HW Supp; U9PA8E - HP
3y Nbd ChnlParts CLJ Ent M65x SVC; U9PA9E - HP
4y Nbd ChnlParts CLJ Ent M65x SVC; U9PB0E - HP
5y Nbd ChnlParts CLJ Ent M65x SVC; U9PB1E - HP
3yNbd+max3 MaintKit CLJEntM65x HWSupp;
U9PB2E - HP 4yNbd+max4 MaintKit CLJEntM65x
HWSupp; U9PB3E - HP 5yNbd+max5 MaintKit
CLJEntM65x HWSupp; U9PB4E - HP 3y NBD
Exchange CLJ Ent M65x SVC; U9PB5E - HP 4y NBD
Exchange CLJ Ent M65x SVC; U9PB6E - HP 5y NBD
Exchange CLJ Ent M65x SVC; U9PB7E - HP 3y
Return CLJ Ent M65x SVC; U9PB8E - HP 4y Return
CLJ Ent M65x SVC; U9PB9E - HP 5y Return CLJ
Ent M65x SVC; U9PC0PE - HP 1y PW Nbd+DMR
CLJ Ent M65x HW Supp; U9PC1PE - HP 2y PW
Nbd+DMR CLJ Ent M65x HW Supp; U9PC2PE - HP
1y PW 4h 9x5+DMR CLJ Ent M65x HW Supp;
U9PC3PE - HP 2y PW 4h 9x5+DMR CLJ Ent M65x
HW Supp; U9PC4PE - HP1y PW 4h 13x5+DMR CLJ
Ent M65x HW Supp; U9PC5PE - HP2y PW 4h
13x5+DMR CLJ Ent M65x HW Supp; U9PC6PE -
HP 1y PW Nbd CTR+DMR CLJEntM65x HW Supp;
U9PC7PE - HP 2y PW Nbd CTR+DMR CLJEntM65x
HW Supp; U9PC8PE - HP 1y PW ChnlParts CLJ Ent
M65x SVC; U9PC9PE - HP 2y PW ChnlParts CLJ
Ent M65x SVC; U9PD0PE - HP 1y PW NBD
Exchange CLJ Ent M65x SVC; U9PD1PE - HP 1y
PW Return CLJ Ent M65x SVC**

**Post
warranty
repair &
maintenance**

Please consult web site <http://www.hp.com/support>

ADVANCED FEATURES

Printer smart software features

Print preview, duplex printing, print multiple pages per sheet (2, 4, 6, 9, 16), collation, watermarks, store print jobs, easy-access USB

Energy savings feature technology

HP Auto-on/Auto-off Technology; Instant-on Technology

SECURITY MANAGEMENT

Security management

Identity management: Kerberos authentication; LDAP authentication; 1000 user PIN codes; optional HP and 3rd party advanced authentication solutions (e.g.; badge readers); Network: IPsec/firewall with Certificate; Pre-Shared Key; and Kerberos authentication; Supports WJA-10 IPsec configuration Plug-in; 802.1X authentication (EAP-PEAP; EAP-TLS); SNMPv3; HTTPS; Certificates; Access Control List; Data: Storage Encryption; Encrypted PDF & Email (uses FIPS 140 validated cryptographic libraries from Microsoft); Secure Erase; SSL/TLS (HTTPS); Encrypted Credentials; Device: Security lock slot; USB port disablement; hardware integration pocket for security solutions; Intrusion Detection with Red Balloon Security Technology - Constant in-device monitoring for attacks; SureStart Secure Boot - BIOS Integrity Checking with self-healing capability; Whitelisting - loads only known good code (DLLs, EXEs, ...); Security management: Compatible with HP JetAdvantage Security Manager, Device Security Syslog Messages processed and accessible in Arcsight and Splunk SIEMs

COMPATIBILITY

Accessories

HP Color LaserJet 550-sheet Paper Feeder P1B09A, HP Color LaserJet 550-sheet Paper Feeder with Stand and Cabinet P1B10A, HP Color LaserJet 3x550-sheet Paper Feeder with Stand P1B11A, HP Color LaserJet 1x550/2000-sheet Feeder and Stand P1B12A, HP Jetdirect 2900nw Print Server J8031A, HP Jetdirect 3000w NFC/Wireless Accessory J8030A, HP Trusted Platform Module Accessory F5S62A, HP Internal USB Ports B5L28A, HP Secure High Performance Hard Disk Drive B5L29A, HP 1GB DDR3 x32 144-Pin 800MHz SODIMM E5K48A, HP Accessibility Assistant 2MU47A

Orderable supplies **HP LaserJet 110V Maintenance Kit P1B91A, HP LaserJet 220V Maintenance Kit P1B92A, HP LaserJet Image Transfer Belt Kit P1B93A, HP LaserJet Toner Collection Unit P1B94A**

PRODUCT NAMES

Sub-brand name **Color LaserJet**
