

# Numark Scratch X Specs

Number of Channels **2 x Stereo**

---

EQ **Channel EQ:**  
Hi  
Mid  
Low

---

Built-In Effects *None*

---

Sample Rates 48 kHz

---

Bit Depths 24-Bit (AD/DA Conversion)  
32-Bit (DSP)

---

## Connectivity

---

Audio Inputs **2 x Stereo RCA Line/Phono Input**  
**1 x Combo XLR-1/4" TRS Input**

---

Audio Outputs **2 x XLR 3-Pin Balanced Master Output**  
**1 x Stereo RCA Unbalanced Master Output**  
**1 x Stereo RCA Booth Output**  
**1 x 1/4" TRS Headphone Output**  
**1 x 1/8" / 3.5 mm TRS Headphone Output**

---

USB **1 x USB Type-B (USB 2.0)**

---

# Performance

---

Frequency Response

**Headphone Output:**

20 Hz to 20 kHz +0.2 dB

**Booth/Master Output:**

20 Hz to 20 kHz +0.2 dB

**Phono Input:**

20 Hz to 20 kHz (RIAA Curve)

**RCA Line Input:**

20 Hz to 20 kHz +0.3 dB

---

Input Level

**RCA Line:**

+7.8 dBV

---

Output Level

**Headphone:**

+14 dBu (Unloaded)

**Master:**

+20 dBu (Max)

**Booth:**

+6 dBV (Max)

---

Headphone Output Power

115 mW per Channel into 32 Ohms

---

I/O Impedance

**Headphone Output:**

32 Ohms

**Booth/Master Output:**

300 Ohms

**RCA Line Input:**

47 Kilohms

**XLR Master Output:**

300 Ohms

---

SNR

**Headphone:**

108 dBA (Max Output)

**Booth/Master:**

107 dBA (Max Output)

**Master:**

108 dBA (Max Output)



Box Dimensions (LxWxH)

17 x 15.3 x 8.6"

---