

## Product description

**Fujikura 90S** is a fusion splicer with a high precision lenses, which provide an accurate core-to-core alignment. Also, these lenses allow the splicer to discriminate between fiber types.

### Features

Splicing time: 7-9 sec (SM FAST mode).

Heat time: 13-15 sec (for 60 mm sleeves).

The faster automated features.

Easy fiber protection sleeve positioning.

The sheath clamp is compatible with loose tube fiber.

Preinstalled operation manual.

Battery life increased up to 500 recharge cycles.

Increased electrode lifetime – up to 5000 splicing cycles with one set.

Dimensions: 170 × 173 × 150 mm.

Weight: 2.8 kg (with battery).

### Package Contents

Fusion Splicer Fujikura 90S — 1 pc.

Battery (BTR-15) — 1 pc.

AC Adaptor (ADC-20) — 1 pc.

AC Power Cord (ACC-14, 15, 16 or 17) — 1 pc.

USB Cable (USB-01) — 1 pc.

Fusion Splicer Strap (ST-02) — 1 pc.

Spare Electrodes (ELCT-16B) — 1 set.

Fiber Holder Set Plate (SP-03) — 1 set.

Carrying Case (CC-39) — 1 pc.

Work Tray Left (WT-09L) — 1 pc.

Work Tray Right (WT-09R) — 1 pc.

Work Tray J-Plate (JP-09) — 1 pc.

Tripod Screw (TS-03) — 1 pc.

Carrying Case Strap (ST-03) — 1 pc.

Alcohol Dispenser (AP-02) — 1 pc.

Quick Reference Guide (QRG-02-E, C or J) — 1 pc.

Single Fiber Stripper (SS-03 or SS-01) — 1 pc.

Optical Fiber Cleaver (CT-50) — 1 pc.

Fiber Scrap Collector (FBD-05) — 1 pc.

Fiber Setting Plate (AD-10-M24) — 1 pc.

Case for Cleaver (CC-37) — 1 pc.

Hexagonal Wrench (HEX-01) — 1 pc.