

## PANEL

Screen Size	55"
Panel Technology	IPS
Aspect Ratio	16 : 9
Native Resolution	1,920 x 1,080 (FHD)
Brightness(Typ.,cd/m <sup>2</sup> )	500
Contrast Ratio	1,200:1
Dynamic CR	500,000 : 1 (The luminosity ratio of Full Black/Full White color on video input condition.)
Viewing Angle (H x V)	178 x 178
Response Time	8 ms (G to G)
Surface Treatment	3%
Life Time (Typ.)	60,000 Hrs
Operation Hours	24 Hrs
Orientation	Landscape & Portrait

## CONNECTIVITY

Input	HDMI(2), DP, DVI-D, Audio, USB
Output	DP, Audio
External Control	RS232C In/out, RJ45(LAN) In, IR In

## MECHANICAL SPECIFICATION

Bezel Color	Black
Bezel Width	2.25 mm (T/L) / 1.25 mm(B/R)
Monitor Dimension (W × H × D)	1,213.4 x 684.2 x 93.1 mm
Weight (Head)	20.3kg
Carton Dimensions (W × H × D)	1,353 x 980 x 263 mm
Packed Weight	33kg
Handle	Yes
VESA™ Standard Mount Interface	600 x 400 mm

## ENVIRONMENT CONDITIONS

Operation Temperature	0°C to 40°C
Operation Humidity	10 % to 80 %

## POWER

Power Supply	100-240V~, 50/60Hz
Power Type	Built-In Power

## POWER CONSUMPTION

Typ. / Max.	130 W / 150 W
Smart Energy Saving	62 W

## CERTIFICATION

Safety	CB / NRTL
EMC	FCC Class "A" / CE / KC

---

ErP / Energy Star

Yes(EU Only) / Energy Star 8.0

---

## MEDIA PLAYER COMPATIBILITY

OPS type compatible

No

---

## SOFTWARE COMPATIBILITY

Content Management Software

SuperSign CMS

---

Control and Monitoring Software

SuperSign Control/Control+

---

## ACCESSORY

Basic

Remote Controller, Power Cord, RS232C Cable, DP Cable, IR Receiver, Guide Bracket, Screws, Manual

---

Optional

Wall Mount (Landscape: WM-L640V, Portrait: WM-P640V)

---

## COMPLIANCE INFORMATION

[Dismantling information\(55VL5F-A\)](#)

---

[EU Energy label 2019\(55VL5F-A\)](#)

---

[EU Energy label 2019\(55VL5F-AK\)](#)

---

[Product information sheet \(55VL5F-A\)](#)

---

[Product information sheet \(55VL5F-AK\)](#)

---

[\*\*MORE COMPLIANCE INFORMATION\*\*](#)

---