

ATEN CE690 Specs

Connectors

CE690L's KVM Ports

Video: 1 x DVI-D female (white)

Speaker: 1 x Mini stereo jack female (green)

Microphone: 1 x Mini stereo jack female (pink)

USB (Keyboard/Mouse): 1 x USB type-B female (white)

USB (Touch Panel): 1 x USB type-B female (white)

CE690L and CE690R's Console Ports

Keyboard: 1 x USB type-A female (white)

Video: 1 x DVI-D female (white)

Mouse: 1 x USB type-A female (white)

Speaker: 1 x Mini stereo jack female (green)

Microphone: 1 x Mini stereo jack female (pink)

USB (Touch Panel): 1 x USB type-A female (white)

Power: 1 x DC jack (black)

Optical In/Out: 1 x bi-directional SFP (LC)

CE690L RS-232: 1 x DB-9 female (black)

CE690R RS-232: 1 x DB-9 male (black)

Indicator LEDs

CE690L: Three green lights for local, remote, and link

CE690R: Two green lights for remote and link

Switches

One pushbutton on CE690L for operation mode selection

One pushbutton on CE690R to wakeup PC

Fiber optic

Operating Distance: 12.4 mile / 20 km with SM fiber

Wavelength: 1310/1550 nm for SM

Data Rate (Single Fiber): 3.125 Gb/s

Power Consumption

CE690L: 5.3 VDC, 10.2 W

CE690R: 5.3 VDC, 9 W

Environmental

Operating Temperature: 32 to 122°F / 0 to 50°C

Storage Temperature: -4 to 140°F / -20 to 60°C

Humidity: 0 to 80% RH, non-condensing

Material of Construction Metal

Dimensions (LxWxH) 8.5 x 6.4 x 1.6" / 21.5 x 16.3 x 4.2 cm

Weight 2.4 lb / 1.1 kg

Packaging Info

Package Weight 8.95 lb
