

Comica Audio BOOMX-D Specs

System

Wireless Transmission	Digital 2.4 GHz
Included Transmitters	2 x Clip-On with Microphone
Diversity	Non-Diversity
RF Frequency Band	2400 to 2483.5 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	164' / 50 m (Line of Sight)
Max Systems per Setup	2
Sample Rate/Resolution	48 kHz / 16-Bit
Latency	<20 ms (Maximum)

Receiver

Form Factor	Camera-Mount
Mounting Options	Belt Clip (with Included Hardware)

Antenna	1 x Internal
Number of Audio Channels	2
Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Mic Output 1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output
Gain Range	0 to 12 dB
USB/Lightning Connectivity	1 x USB Type-C (Bus Power, Charging)
Approximate RF Sensitivity	-86 dBm
RF Output Power	10 mW
Power Requirements	Battery
Battery Type	1 x Built-In Rechargeable
Internal Battery Capacity	300 mAh
Approx. Battery Life	5 Hours (Lithium Rechargeable)
Display & Indicators	1 x LCD (AF Level, Battery Status, Output Level)
Housing	Plastic
Operating Temperature	32 to 122°F / 0 to 50°C
Dimensions	1.5 x 0.9 x 2.2" / 39 x 22 x 55 mm

Weight	1 oz / 29 g
--------	-------------

Transmitter

Form Factor	Clip-On with Microphone
-------------	-------------------------

RF Output Power	10 mW
-----------------	-------

Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Input
-----------	--

Muting	Off/On Switch
--------	---------------

Auto-Level Control	No
--------------------	----

Frequency Response	80 Hz to 20 kHz
--------------------	-----------------

Antenna	1 x Internal
---------	---------------------

Approximate RF Sensitivity	-86 dBm
----------------------------	---------

Power Requirements	Battery, Bus Power (USB)
--------------------	--------------------------

Battery Type	1 x Built-In Rechargeable
--------------	----------------------------------

Internal Battery Capacity	300 mAh
---------------------------	---------

Approx. Battery Life	5 Hours (Lithium Rechargeable)
----------------------	--------------------------------

USB/Lightning Connectivity	1 x USB Type-C (Bus Power, Charging)
----------------------------	---

Display & Indicators	1 x LCD (Audio Level, Battery Status, Mute, Signal Strength)
----------------------	---

Housing	Plastic
---------	---------

Operating Temperature	32 to 122°F / 0 to 50°C
-----------------------	-------------------------

Dimensions	1.5 x 0.9 x 2.2" / 39 x 22 x 55 mm
------------	------------------------------------

Weight	1 oz / 29 g
--------	-------------

Microphone

Form Factor	Integrated
-------------	------------

Sound Field	Mono
-------------	------

Polar Pattern	Omnidirectional
---------------	-----------------

Microphone 2

Form Factor	Lavalier
-------------	----------

Sound Field	Mono
-------------	------

Polar Pattern	Omnidirectional
---------------	-----------------

Output Connectors	1 x 1/8" / 3.5 mm TRS Male Unbalanced
-------------------	--

Packaging Info

Package Weight 0.96 lb

Box Dimensions (LxWxH) 7.2 x 4.2 x 2.8"
