

# Comica Audio BOOMX-D Specs

## System

---

Wireless Transmission	Digital 2.4 GHz
Included Transmitters	<b>1 x</b> Clip-On with Microphone
Diversity	Non-Diversity
RF Frequency Band	2400 to 2483.5 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	164' / 50 m (Line of Sight)
Max Systems per Setup	2
Sample Rate/Resolution	48 kHz / 16-Bit
Latency	<20 ms (Maximum)

---

## Receiver

---

Form Factor	Plug-In
Mounting Options	Plug-In

---

Antenna	<b>1 x</b> Internal
Number of Audio Channels	2
Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output
Gain Range	0 to 12 dB
USB/Lightning Connectivity	<b>1 x</b> USB Type-C (Audio, Bus Power)
RF Output Power	10 mW
Power Requirements	Bus Power (USB)
Display & Indicators	<b>1 x</b> LCD (AF Level, Battery Status, Output Level)
Housing	Plastic
Operating Temperature	32 to 122°F / 0 to 50°C
Dimensions	1.3 x 0.5 x 2.8" / 33 x 13 x 70 mm
Weight	0.7 oz / 19 g

## Transmitter

---

Form Factor	Clip-On with Microphone
RF Output Power	10 mW

---

Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Input
Muting	Off/On Switch
Auto-Level Control	No
Frequency Response	80 Hz to 20 kHz
Antenna	<b>1 x</b> Internal
Approximate RF Sensitivity	-86 dBm
Power Requirements	Battery, Bus Power (USB)
Battery Type	<b>1 x</b> Built-In Rechargeable
Internal Battery Capacity	300 mAh
Approx. Battery Life	5 Hours (Lithium Rechargeable)
USB/Lightning Connectivity	<b>1 x</b> USB Type-C (Bus Power, Charging)
Display & Indicators	<b>1 x</b> LCD (Audio Level, Battery Status, Mute, Signal Strength)
Housing	Plastic
Operating Temperature	32 to 122°F / 0 to 50°C
Dimensions	1.5 x 0.9 x 2.2" / 39 x 22 x 55 mm

---

Weight

1 oz / 29 g

---

## Microphone

---

Form Factor

Integrated

---

Sound Field

Mono

---

Polar Pattern

Omnidirectional

---

## Packaging Info

---

Package Weight

0.62 lb

---

Box Dimensions (LxWxH)

5.5 x 4.3 x 2.8"

---