

# Comica Audio BOOMX-D RX Specs

Wireless Transmission	Digital 2.4 GHz
Diversity	Non-Diversity
RF Frequency Band	2400 to 2483.5 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	164' / 50 m (Line of Sight)
Max Systems per Setup	2
Latency	<20 ms (Maximum)

## Receiver

Form Factor	Camera-Mount
Mounting Options	Belt Clip (with Included Hardware)
Antenna	<b>1 x</b> Internal
Number of Audio Channels	2
Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Mic Output

**1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output**

---

Gain Range 0 to 12 dB

---

USB/Lightning Connectivity **1 x USB Type-C (Bus Power, Charging)**

---

Approximate RF Sensitivity -86 dBm

---

RF Output Power 10 mW

---

Power Requirements Battery

---

Battery Type **1 x Built-In Rechargeable**

---

Internal Battery Capacity 300 mAh

---

Approx. Battery Life 5 Hours (Lithium Rechargeable)

---

Display & Indicators **1 x LCD (AF Level, Battery Status, Output Level)**

---

Housing Plastic

---

Operating Temperature 32 to 122°F / 0 to 50°C

---

Dimensions 1.5 x 0.9 x 2.2" / 39 x 22 x 55 mm

---

Weight 1 oz / 29 g

---

## Packaging Info

---

Package Weight 0.205 lb

---

Box Dimensions (LxWxH) 5 x 4 x 1.2"

---