

Comica Audio CVM-WM200C Specs

System

Wireless Transmission	Digital UHF
Number of RF Channels	96
Included Transmitters	1 x Bodypack with Microphone
Diversity	Non-Diversity
RF Frequency Band	A: 520 to 548.5 MHz B: 550 to 578.5 MHz
RF Bandwidth	Up to 57 MHz
RF Channel Scanning	Auto-Scan
Max Operating Range	393.7' / 120 m (Line of Sight) 262.5' / 80 m (with Obstruction)
Max Systems per Setup	2
Latency	<20 ms
Encryption	<i>None</i>

Modulation FM

Receiver

Form Factor Camera-Mount

Mounting Options Belt Clip, Shoe-Mount (with Included Hardware)

Antenna **2 x** 1/4 Wave External, Fixed (Top-Mount)

Number of Audio Channels 2

Audio I/O **1 x** 1/8" / 3.5 mm TRS Female Unbalanced Line Output (Lockable)
1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Lockable)

Spurious Emission: < -60 dBc

Power Requirements Battery

Battery Type **2 x** AA (Not Included)

Display & Indicators **1 x** Backlit LCD (AF Level, Battery Status, Channel, Group, Level, Power, RF Level, Sync, Transmitter Battery Status)
2 x LED (Data Transmission, Sync)

Housing Metal

Operating Temperature 32 to 122°F / 0 to 50°C

Storage Temperature -4 to 140°F / -20 to 60°C

Dimensions 2.5 x 3.3 x 0.9" / 63.5 x 84 x 23 mm (without Antennas)

Transmitter

Form Factor Bodypack with Microphone

RF Output Power 10 / 30 mW

Audio I/O **1 x** 1/8" / 3.5 mm TRS Female Unbalanced Input (Lockable)

Pad *None*

Muting Off/On Switch

Auto-Level Control No

Signal Processing **High-Pass Filter:**

Sync Method IR

Antenna **1 x** 1/4 Wave External, Fixed

Power Requirements Battery

Battery Type **2 x** AA (Not Included)

Display & Indicators **1 x** Backlit LCD (Audio Level, Battery Status, Channel,

Group, Mute, Power, RF Output Power)

1 x LED (Audio Level)

1 x LED (Sync)

Housing

Metal

Operating Temperature

32 to 122°F / 0 to 50°C

Storage Temperature

-4 to 140°F / -20 to 60°C

Dimensions

2.5 x 3.3 x 0.9" / 63.5 x 84 x 23 mm (without Antennas)

Microphone

Form Factor

Lavalier

Color

Black

Sound Field

Mono

Operating Principle

Pressure Operated

Capsule

Electret Condenser

Polar Pattern

Omnidirectional

Frequency Range

30 Hz to 20 kHz

SNR

65 dB

Maximum SPL	100 dB SPL
Sensitivity	-35 dB
Output Connectors	1 x 1/8" / 3.5 mm TRS Male Unbalanced (Lockable)
Cable Length	3.94' / 1.2 m

Packaging Info

Package Weight	3.965 lb
Box Dimensions (LxWxH)	14.9 x 8.4 x 3.6"