

Comica Audio CVM-WM200TX Specs

Wireless Transmission

Analog UHF

RF Frequency Band

A:
520 to 548.5 MHz
B:
550 to 578.5 MHz

RF Bandwidth

Up to 57 MHz

Max Operating Range

393.7' / 120 m (Line of Sight)
262.5' / 80 m (with Obstruction)

Latency

20 ms

Encryption

None

Modulation

FM

Transmitter

Form Factor

Bodypack

RF Output Power

10 / 30 mW

Audio I/O

1 x 1/8" / 3.5 mm TRS Female Unbalanced Input
(Lockable)

Muting	Off/On Switch
Auto-Level Control	No
Signal Processing	High-Pass Filter:
Sync Method	IR
Antenna	1 x 1/4 Wave External, Fixed
Power Requirements	Battery
Battery Type	2 x AA (Not Included)
Display & Indicators	1 x Backlit LCD (Audio Level, Battery Status, Channel, Group, Mute, Power, RF Output Power) 1 x LED (Audio Level) 1 x LED (Sync)
Housing	Metal
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Dimensions	2.5 x 3.3 x 0.9" / 63.5 x 84 x 23 mm (without Antennas)

Microphone

Form Factor	Lavalier
-------------	----------

Color	Black
Sound Field	Mono
Capsule	Electret Condenser
Polar Pattern	Omnidirectional
Frequency Range	30 Hz to 20 kHz
SNR	65 dB
Maximum SPL	100 dB SPL
Sensitivity	-35 dB
Output Connectors	1 x 1/8" / 3.5 mm TRS Male Unbalanced (Lockable)
Cable Length	3.94' / 1.2 m

Packaging Info

Package Weight	0.43 lb
Box Dimensions (LxWxH)	8.4 x 3.6 x 1.8"