

Comica Audio CVM-WM200/300 XLR Specs

Wireless Transmission

Digital UHF

RF Frequency Band

A:
520 to 548 MHz
B:
550 to 578.5 MHz

RF Bandwidth

Up to 56.5 MHz

Max Operating Range

196.9' / 60 m
98.4' / 30 m

Latency

<20 ms

Encryption

None

Transmitter

Form Factor

Plug-On

RF Output Power

10 / 30 mW

Audio I/O

1 x XLR 3-Pin Female Balanced Input (Lockable)

Phantom Power

+48 V \pm 2 V

Pad

None

Muting	Off/On Switch
Signal Processing	High-Pass Filter:
Frequency Response	20 Hz to 18 kHz
Sync Method	IR
Antenna	1 x Internal
Power Requirements	Battery
Battery Type	2 x AA (Not Included)
Approx. Battery Life	4 Hours
USB/Lightning Connectivity	<i>None</i>
Display & Indicators	1 x Backlit LCD (Audio Level, Battery Status, Channel, Group, Mute, Phantom Power, Power, RF Output Power) 1 x LED (Signal Strength) 1 x LED (Sync)
Housing	Metal
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Dimensions	2.5 x 4.5 x 1.4" / 62.4 x 114.8 x 34.3 mm

Packaging Info

Package Weight 0.49 lb

Box Dimensions (LxWxH) 5.9 x 3.5 x 2.6"
