

Comica Audio CVM-WM100 Specs

System

Wireless Transmission	Analog UHF
Number of RF Channels	48
Included Transmitters	1 x Bodypack with Microphone
Diversity	Non-Diversity
RF Frequency Band	520 to 534.1 MHz
RF Bandwidth	Up to 14.1 MHz
Max Operating Range	328.1' / 100 m (Line of Sight) 196.9' / 60 m (with Obstruction)
Max Systems per Setup	5
Latency	<40 ms
Encryption	<i>None</i>
Modulation	FM

Receiver

Form Factor	Camera-Mount
Mounting Options	Belt Clip, Shoe-Mount (with Included Hardware)
Antenna	1 x 1/4 Wave External, Fixed (Top-Mount)
Number of Audio Channels	1
Audio I/O	1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Lockable) 1 x 1/8" / 3.5 mm TRS Female Unbalanced Line Output (Lockable)
Frequency Response	20 Hz to 18 kHz
Power Requirements	Battery
Battery Type	2 x AA (Not Included)
Display & Indicators	1 x Backlit LCD (AF Level, Battery Status, Channel, Frequency, Level, Power, RF Level, Sync) 1 x LED (Sync)
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Dimensions	2.6 x 4.4 x 1" / 65 x 111.5 x 25.3 mm (without Antennas)

Transmitter

Form Factor	Bodypack with Microphone
RF Output Power	15 / 30 mW
Audio I/O	2 x 1/8" / 3.5 mm TRS Female Unbalanced Input (Lockable)
Pad	<i>None</i>
Muting	Off/On Switch
Signal Processing	High-Pass Filter:
Sync Method	Manual
Antenna	1 x 1/4 Wave External, Fixed
Power Requirements	Battery
Battery Type	2 x AA (Not Included)
USB/Lightning Connectivity	<i>None</i>
Display & Indicators	1 x Backlit LCD (Audio Level, Battery Status, Channel, Mute, Power, Signal Strength) 1 x LED (Sync)
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C

Dimensions	2.6 x 4.4 x 1" / 65 x 111.5 x 25.3 mm (without Antennas)
------------	--

Microphone

Form Factor	Lavalier
-------------	----------

Sound Field	Mono
-------------	------

Operating Principle	Pressure Operated
---------------------	-------------------

Capsule	Electret Condenser
---------	--------------------

Polar Pattern	Omnidirectional
---------------	-----------------

Frequency Range	30 Hz to 20 kHz
-----------------	-----------------

SNR	65 dB
-----	-------

Maximum SPL	100 dB SPL
-------------	------------

Sensitivity	-35 dB
-------------	--------

Output Connectors	1 x 1/8" / 3.5 mm TRS Male Unbalanced (Lockable)
-------------------	---

Cable Length	3.94' / 1.2 m
--------------	---------------

Packaging Info

Package Weight 1.55 lb

Box Dimensions (LxWxH) 11.4 x 8.9 x 3.1"
