Comica Audio CVM-WM100H HTX+RX Specs

System

| Wireless Transmission | Analog UHF |
|-----------------------|--|
| Number of RF Channels | 48 |
| Included Transmitters | 1 x Handheld |
| Diversity | Non-Diversity |
| RF Frequency Band | 520 to 534.1 MHz |
| RF Bandwidth | 14.1 MHz |
| RF Channel Scanning | Manual |
| Max Operating Range | 328.1' / 100 m (Line of Sight) 196.9' / 60 m (with Obstruction) |
| Max Systems per Setup | 5 |
| Latency | <20 ms |
| Modulation | FM |
| | |

Receiver

| Form Factor | Camera-Mount |
|--------------------------|--|
| Mounting Options | Belt Clip, Shoe-Mount, 1/4"-20 Female (with Included Hardware) |
| Antenna | 1 x 1/4 Wave External, Fixed (Top-Mount) |
| Number of Audio Channels | 1 |
| Audio I/O | 1 x 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output (Lockable) 1 x 1/8" / 3.5 mm TRS Female Unbalanced Output (Lockable) |
| Frequency Response | 20 Hz to 18 kHz |
| Power Requirements | Battery |
| Battery Type | 2 x AA (Not Included) |
| Approx. Battery Life | 4 Hours (Alkaline) |
| Display & Indicators | 1 x Backlit LCD (AF Level, Battery Status, Channel, Frequency, Level, Power, RF Level, Sync) 1 x LED (Sync) |
| Operating Temperature | 32 to 122°F / 0 to 50°C |
| Storage Temperature | -4 to 140°F / -20 to 60°C |
| Dimensions | 2.6 x 4.4 x 1" / 65 x 111.5 x 25.3 mm (without Antennas) |

Transmitter

| Form Factor | Handheld |
|-----------------------|---|
| RF Output Power | 15 mW |
| Audio I/O | None |
| Muting | Off/On Switch |
| Auto-Level Control | No |
| Signal Processing | High-Pass Filter: |
| Sync Method | Manual |
| Antenna | 1 x 1/4 Wave Internal, Fixed |
| Power Requirements | Battery |
| Battery Type | 2 x AA (Not Included) |
| Approx. Battery Life | 6 Hours (Alkaline) |
| Display & Indicators | 1 x Backlit LCD (Audio Level, Battery Status, Channel, High-Pass Filter, Mute, Power, RF Output Power) 1 x LED (Sync) |
| Operating Temperature | 32 to 122°F / 0 to 50°C |
| Storage Temperature | -4 to 140°F / -20 to 60°C |

Microphone

| Form Factor | Handheld Capsule |
|---------------------|-------------------|
| Sound Field | Mono |
| Operating Principle | Pressure Operated |
| SNR | 65 dB |
| THD | 5% |

Packaging Info

| Package Weight | 2.15 lb |
|------------------------|--------------------|
| Box Dimensions (LxWxH) | 11.5 x 8.38 x 3.38 |