

# Comica Audio CVM-WS60-COMBO Specs

## System

---

Wireless Transmission	Analog UHF
Number of RF Channels	24
Included Transmitters	<b>2 x</b> Bodypack with Microphone
Diversity	Non-Diversity
RF Frequency Band	<b>A:</b> 568.125 to 579.125 MHz <b>B:</b> 580.125 to 591.125 MHz
RF Bandwidth	11 MHz
Max Operating Range	196.9' / 60 m (Line of Sight) 98.4' / 30 m (with Obstruction)
Latency	<40 ms
Encryption	<i>None</i>
Modulation	FM

---

## Receiver

---

Form Factor	Camera-Mount / Portable
Mounting Options	Shoe-Mount, Tabletop (with Included Hardware)
Antenna	<b>1 x</b> Internal, Fixed
Number of Audio Channels	2
Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Line Output <b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output
Frequency Response	20 Hz to 18 kHz
USB/Lightning Connectivity	<b>1 x</b> USB Type-C (Bus Power, Charging)
Power Requirements	Battery or Bus Power (USB)
Battery Type	<b>3 x</b> AAA (Not Included)
Approx. Battery Life	4 Hours
AC/DC Power Adapter	5 VDC (Not Included)
Display & Indicators	<b>1 x</b> Backlit LCD (Battery Status, Channel, Data Transmission, Group, Level, RF Level) <b>2 x</b> LED (Data Transmission)
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C

---

Dimensions	4.1 x 2.6 x 0.7" / 104 x 65.2 x 18 mm
------------	---------------------------------------

---

## Transmitter

---

Form Factor	Bodypack with Microphone
-------------	--------------------------

---

RF Output Power	10 mW
-----------------	-------

---

Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Input
-----------	--

---

Pad	<i>None</i>
-----	-------------

---

Muting	Off/On Switch
--------	---------------

---

Signal Processing	<b>High-Pass Filter:</b>
-------------------	--------------------------

---

Sync Method	Manual
-------------	--------

---

Antenna	<b>1 x</b> Internal, Fixed
---------	----------------------------

---

Power Requirements	Battery or Bus Power (USB)
--------------------	----------------------------

---

Battery Type	<b>3 x</b> AAA (Not Included)
--------------	-------------------------------

---

Approx. Battery Life	4 Hours
----------------------	---------

---

USB/Lightning Connectivity	<b>1 x</b> USB Type-C (Bus Power, Charging)
----------------------------	---

---

Display & Indicators	<b>1 x</b> Backlit LCD (Audio Level, Battery Status, Channel,
----------------------	---

Group, High-Pass Filter, Mute, RF Output Power)  
**1 x** LED (RF Output Power)

---

Operating Temperature 32 to 122°F / 0 to 50°C

---

Storage Temperature -4 to 140°F / -20 to 60°C

---

Dimensions 4.1 x 2.6 x 0.7" / 104 x 65.2 x 18 mm

---

## Microphone

---

Form Factor Lavalier

---

Color Black

---

Sound Field Mono

---

Output Connectors **1 x** 1/8" / 3.5 mm TRS Male Unbalanced

---

## Packaging Info

---

Package Weight 2.055 lb

---

Box Dimensions (LxWxH) 9.7 x 7.3 x 4"

---