

# Comica Audio CVM-WS50B Specs

## System

---

Wireless Transmission	Analog UHF
Number of RF Channels	6
Included Transmitters	<b>1 x</b> Bodypack with Microphone
Diversity	Non-Diversity
RF Frequency Band	520 to 526 MHz
RF Bandwidth	6 MHz
RF Channel Scanning	Manual
Max Operating Range	196.9' / 60 m (Line of Sight) 98.4' / 30 m (with Obstruction)
Max Systems per Setup	2
Latency	<40 ms
Encryption	<i>None</i>

---

## Receiver

---

Form Factor	Portable
Mounting Options	Mic Stand, Shoe-Mount (with Optional Hardware)
Antenna	<b>1 x</b> 1/4 Wave Wire, Fixed
Number of Audio Channels	1
Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Line Output <b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Headphone Output
Frequency Response	20 Hz to 18 kHz
USB/Lightning Connectivity	<b>1 x</b> Micro-USB (Bus Power, Charging)
Power Requirements	Battery or Bus Power (USB)
Battery Type	<b>1 x</b> Built-In Rechargeable (Included)
Internal Battery Capacity	1150 mAh
Approx. Battery Life	8 Hours
Display & Indicators	<b>1 x</b> LCD (Battery Status, Channel, Level) <b>1 x</b> LED (Sync)
Dimensions	4.1 x 2.3 x 0.6" / 104 x 57.6 x 16.3 mm

---

# Transmitter

---

Form Factor	Bodypack with Microphone
RF Output Power	10 mW
Audio I/O	<b>1 x</b> 1/8" / 3.5 mm TRS Female Unbalanced Input
Muting	Off/On Switch
Auto-Level Control	No
Sync Method	Manual
Antenna	<b>1 x</b> 1/4 Wave Wire, Fixed
Power Requirements	Battery
Battery Type	<b>1 x</b> Rechargeable (Included)
Internal Battery Capacity	1150 mAh
Approx. Battery Life	8 Hours
USB/Lightning Connectivity	<b>1 x</b> Micro-USB (Charging)
Display & Indicators	<b>1 x</b> LCD (Audio Level, Battery Status, Channel, Mute, Power) <b>1 x</b> LED (Sync)
Dimensions	3.3 x 2.3 x 0.6" / 85 x 59 x 16.3 mm

---

## Microphone

---

Form Factor

Lavalier

Sound Field

Mono

Output Connectors

**1 x** 1/8" / 3.5 mm TRS Male Unbalanced

Cable Length

45" / 114.30 cm

---

## Packaging Info

---

Package Weight

1.435 lb

Box Dimensions (LxWxH)

9.65 x 7.95 x 2.65"

---