

Comica Audio CVM-WS50H Specs

Receiver

Channels	6 (0 to 5)
Wireless Frequency Range	520 to 526 MHz
Receiving Range	Maximum: 197' / 60 m Optimal: 98.4' / 30 m
Signal-to-Noise Ratio (SNR)	> 65 dB
Antenna	1/4 Wavelength Wire Antenna
Receiving Sensitivity	-95 dBm
Delay	< 20 ms
Audio Distortion	< 0.5%
Frequency Response	20 Hz to 18 kHz
Output Connector	1 x 1/8" / 3.5 mm TRS Line 1 x 1/8" / 3.5 mm TRS Headphone
Battery	LiPo (3.7 V, 1150 mAh)
Battery Life	Up to 8 Hours

Charging Port	Micro-USB
Operating Temperature	32 to 122°F / 0 to 50°C
Storage Temperature	-4 to 140°F / -20 to 60°C
Dimensions (W x H x D)	4.1 x 2.3 x 0.6" / 104.0 x 57.6 x 16.3 mm
Weight	Not Specified by Manufacturer

Transmitter

Channels	6 (0 to 5)
Wireless Frequency Range	520 to 526 MHz
Transmission Range	Maximum: 197' / 60 m Optimal: 98.4' / 30 m
Signal-to-Noise Ratio (SNR)	> 65 dB
Antenna	PCB Antenna
Stray Radiation	< -60 dBc
Delay	< 20 ms
Audio Distortion	< 0.5%
Battery	2 x AA Batteries (Available Separately)

Battery Life

Up to 4 Hours

Operating Temperature

32 to 122°F / 0 to 50°C

Storage Temperature

-4 to 140°F / -20 to 60°C

Dimensions (Diam. x L)

2.1 x 9.8" / 5.4 x 24.8 cm

Weight

Not Specified by Manufacturer

Packaging Info

Package Weight

2.04 lb

Box Dimensions (LxWxH)

12.1 x 8.2 x 3"
