

Comica Audio TRAXSHOT Specs

Microphone

Form Factor	Camera-Mount
Sound Field	Mono, Stereo
Stereo/Surround Configuration	X/Y
Capsule	2 x Electret Condenser
Polar Pattern	Supercardioid
Pattern Selection	Switched (Adjustable on Mic)
Orientation	End Address
High-Pass Filter	Yes
Gain Adjustment	Yes
Indicators	1 x Multi-Segment LED (Battery, Status)
On-Board Controls	Gain/Sensitivity, Polar Pattern
Windscreen	Built-In, Windssock/Windjammer (Included)

Performance

Frequency Range	20 Hz to 20 kHz
Maximum SPL	100 dB SPL
Impedance	600 Ohms
Sensitivity	-40 dB
Signal-to-Noise Ratio	60 dB

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRS Female (on Mic) 1 x 1/8" / 3.5 mm TRS Male (on Detachable Cable) 1 x 1/8" / 3.5 mm TRRS Male (on Detachable Cable)
----------------------------	---

Headphone Connector	1 x 1/8" / 3.5 mm
---------------------	--------------------------

Power

Operating Voltage	Not Specified by Manufacturer
-------------------	-------------------------------

Battery Type	1 x Built-In (Included)
--------------	--------------------------------

Battery Chemistry	Lithium-Ion
-------------------	-------------

Approximate Battery Life	20 Hours
--------------------------	----------

Physical

Mounting	Camera/Shoe-Mount (via Integrated Hardware)
----------	---

Construction Material	Metal
-----------------------	-------

Dimensions	H: 2.4 x W: 2.6 x L: 4.8" / H: 62 x W: 65 x L: 122 mm
------------	---

Weight	4.6 oz / 130 g
--------	----------------

Packaging Info

Package Weight	0.905 lb
----------------	----------

Box Dimensions (LxWxH)	7 x 4.5 x 3.6"
------------------------	----------------
