Comica Audio CVM-VM20 Specs

Microphone

Form Factor	Camera-Mount
Sound Field	Mono
Operating Principle	Pressure Gradient
Capsule	1 x Electret Condenser
Polar Pattern	Supercardioid
Orientation	End Address
Circuitry	Solid-State
Pad	None
High-Pass Filter	75 Hz 150 Hz
Tone Adjustment	None
Gain Adjustment	Up to +20 dB
Indicators	1 x Single LED (Status) 1 x OLED (Battery)

WindscreenFoam (Included)PerformanceFrequency Range20 Hz to 20 kHzMaximum SPL105 dB SPLSensitivity-43 dB (Min Gain) -23 dB (Max Gain)Signal-to-Noise Ratio75 dBConnectivityOutput Connectors (Analog)1 x 1/8" / 3.5 mm TRRS Female (on Mic)Headphone ConnectorNonePowerOperating VoltageNot Specified by ManufacturerBattery Type1 x Built-In	On-Board Controls	Gain, High-Pass Filter, On/Off
Frequency Range20 Hz to 20 kHzMaximum SPL105 dB SPLSensitivity-43 dB (Min Gain) -23 dB (Max Gain)Signal-to-Noise Ratio75 dBConnectivityOutput Connectors (Analog)1 x 1/8" / 3.5 mm TRRS Female (on Mic)Headphone ConnectorNonePowerOperating VoltageNot Specified by Manufacturer	Windscreen	Foam (Included)
Frequency Range20 Hz to 20 kHzMaximum SPL105 dB SPLSensitivity-43 dB (Min Gain) -23 dB (Max Gain)Signal-to-Noise Ratio75 dBConnectivityOutput Connectors (Analog)1 x 1/8" / 3.5 mm TRRS Female (on Mic)Headphone ConnectorNonePowerOperating VoltageNot Specified by Manufacturer		
Maximum SPL 105 dB SPL Sensitivity -43 dB (Min Gain) -23 dB (Max Gain) Signal-to-Noise Ratio 75 dB Connectivity Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRRS Female (on Mic) Headphone Connector None POwer	Performance	
Sensitivity -43 dB (Min Gain) -23 dB (Max Gain) Signal-to-Noise Ratio 75 dB Connectivity 0utput Connectors (Analog) 1 x 1/8" / 3.5 mm TRRS Female (on Mic) Headphone Connector None Power Operating Voltage Not Specified by Manufacturer	Frequency Range	20 Hz to 20 kHz
-23 dB (Max Gain) Signal-to-Noise Ratio 75 dB Connectivity Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRRS Female (on Mic) Headphone Connector None Power	Maximum SPL	105 dB SPL
Connectivity Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRRS Female (on Mic) Headphone Connector None Power Operating Voltage Not Specified by Manufacturer	Sensitivity	
Output Connectors (Analog) 1 x 1/8" / 3.5 mm TRRS Female (on Mic) Headphone Connector None Power Operating Voltage Not Specified by Manufacturer	Signal-to-Noise Ratio	75 dB
Headphone Connector None Power	Connectivity	
Power Operating Voltage Not Specified by Manufacturer	Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRRS Female (on Mic)
Operating Voltage Not Specified by Manufacturer	Headphone Connector	None
	Power	
Battery Type 1 x Built-In	Operating Voltage	Not Specified by Manufacturer
	Battery Type	1 x Built-In

Battery Chemistry	Lithium-Ion
Battery Capacity	300 mAh
Physical	
Color	Black
Mounting	Camera/Shoe-Mount, Shockmount (with Included Hardware)
Construction Material	Metal
Dimensions	ø: 0.9 x L: 7" / ø: 22 x L: 177 mm
Weight	3 oz / 84 g
Packaging Info	
Package Weight	1.205 lb

Box Dimensions (LxWxH)

9 x 5.4 x 4"