

Comica Audio CVM-V20 Specs

Microphone

Form Factor	Camera-Mount
Sound Field	Mono
Capsule	1 x Electret Condenser
Polar Pattern	Supercardioid
Orientation	End Address
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Tone Adjustment	<i>None</i>
Gain Adjustment	+10 dB
Indicators	1 x Red Single LED (Status)
On-Board Controls	Gain, On/Off
Windscreen	Foam (Included)

Performance

Frequency Range 100 Hz to 12 kHz

Maximum SPL 120 dB SPL

Impedance 680 Ohms \pm 30%

Sensitivity -28 dB
-38 dB ⓘ

Signal-to-Noise Ratio 55 dB

THD < 1%

Connectivity

Output Connectors (Analog) **1 x** 1/8" / 3.5 mm TRS Male (on Attached Cable)

Headphone Connector *None*

Power

Operating Voltage 3 V

Battery Type **1 x** 3 V Button (CR2032)

Approximate Battery Life 60 Hours

Physical

Mounting	Camera/Shoe-Mount (via Integrated Hardware)
----------	---

Construction Material	Anodized Aluminum
-----------------------	-------------------

Dimensions	H: 2.53 x W: 1.17 x L: 5.24" / H: 64.3 x W: 29.7 x L: 133 mm
------------	--

Weight	3.25 oz / 92 g
--------	----------------

Packaging Info

Package Weight	0.355 lb
----------------	----------

Box Dimensions (LxWxH)	7.3 x 3.8 x 2.4"
------------------------	------------------
