

Comica Audio CVM-VM10 Specs

Microphone

Primary Applications	Recording to Mobile Device, Audio for Video
----------------------	---

Form Factor	Camera-Mount / Shotgun Mic
-------------	----------------------------

Sound Field	Mono
-------------	------

Capsule	Electret Condenser
---------	--------------------

Polar Pattern	Supercardioid
---------------	---------------

High-Pass Filter	<i>None</i>
------------------	-------------

Gain Adjustment	<i>None</i>
-----------------	-------------

Windscreen	Foam, Windsock/Windjammer (Included)
------------	--------------------------------------

Performance

Frequency Range	80 Hz to 16 kHz
-----------------	-----------------

Maximum SPL	100 dB SPL
-------------	------------

Impedance	22 Kilohms \pm 30%
-----------	----------------------

Sensitivity	-34 dB ⓘ
-------------	----------

Dynamic Range	100 dB
---------------	--------

Signal-to-Noise Ratio	58 dB
-----------------------	-------

THD	< 1%
-----	------

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRRS (on Detachable Cable) 1 x 1/8" / 3.5 mm TRS (on Detachable Cable)
----------------------------	---

Headphone Connector	<i>None</i>
---------------------	-------------

Power

Bus Power	<i>None</i>
-----------	-------------

Operating Voltage	Not Specified by Manufacturer
-------------------	-------------------------------

Physical

Mounting	Camera/Shoe-Mount, Shockmount (Included)
----------	--

Included Case	Soft Case
---------------	-----------

Construction Material	Aluminum
-----------------------	----------

Dimensions

W: 0.8 x L: 3.3" / W: 2.1 x L: 8.5 cm

Weight

1.2 oz / 34.2 g

Packaging Info

Package Weight

0.5 lb

Box Dimensions (LxWxH)

6.3 x 5 x 3.3"
