

Comica Audio CVM-VM10-K2 PRO Specs

Microphone

Form Factor	Mobile Device Mic
Sound Field	Mono
Capsule	1 x Electret Condenser
Polar Pattern	Cardioid
Orientation	End Address
Circuitry	Solid-State
High-Pass Filter	<i>None</i>
Gain Adjustment	<i>None</i>
On-Board Controls	<i>None</i>
Windscreen	Foam, Windsock/Windjammer (Included)

Performance

Frequency Range	60 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	105 dB SPL
-------------	------------

Sensitivity	-33 dB
-------------	--------

Signal-to-Noise Ratio	75 dB
-----------------------	-------

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRS Female (on Mic)
----------------------------	--

Headphone Connector	<i>None</i>
---------------------	-------------

Power

Operating Voltage	1 to 10 V (Plug-In Power)
-------------------	---------------------------

Physical

Mounting	Shockmount (with Included Hardware)
----------	-------------------------------------

Operating Temperature	32 to 122°F / 0 to 50°C
-----------------------	-------------------------

Dimensions	∅: 0.8 x L: 3.3" / ∅: 21 x L: 85 mm
------------	-------------------------------------

Weight	0.1 lb / 34.2 g
--------	-----------------

Packaging Info

Package Weight 1.505 lb

Box Dimensions (LxWxH) 11.8 x 7.9 x 3.1"
