

Comica Audio CVM-VM10 Specs

Microphone

Form Factor	Camera-Mount
Sound Field	Mono
Capsule	1 x Condenser
Polar Pattern	Cardioid
Orientation	End Address
Circuitry	Solid-State
Pad	<i>None</i>
High-Pass Filter	<i>None</i>
Tone Adjustment	<i>None</i>
Gain Adjustment	<i>None</i>
Indicators	<i>None</i>
On-Board Controls	<i>None</i>
Windscreen	Foam, Windsock/Windjammer (Included)

Performance

Frequency Range 60 Hz to 20 kHz

Maximum SPL 105 dB SPL

Sensitivity -33 dB

Signal-to-Noise Ratio 75 dB

Connectivity

Output Connectors (Analog) **1 x** 1/8" / 3.5 mm TRS Female (on Mic)

Headphone Connector *None*

Power

Operating Voltage 1 to 10 V

Physical

Color Black

Mounting Shockmount (via Integrated Hardware)

Included Case	Zipper Pouch
---------------	--------------

Construction Material	Aluminum, Metal
-----------------------	-----------------

Packaging Info

Package Weight	1.25 lb
----------------	---------

Box Dimensions (LxWxH)	9.6 x 7.9 x 2.6"
------------------------	------------------
