

Comica Audio CVM-VS10 Specs

Microphone

Primary Applications	ENG (Electronic News Gathering), Audio for Video, Location Sound
----------------------	--

Form Factor	Plug-In Mount
-------------	---------------

Sound Field	Stereo
-------------	--------

Stereo/Surround Configuration	X/Y
-------------------------------	-----

Capsule	2 x Electret Condenser
---------	-------------------------------

Polar Pattern	Cardioid
---------------	----------

Orientation	End Address
-------------	-------------

High-Pass Filter	<i>None</i>
------------------	-------------

Gain Adjustment	<i>None</i>
-----------------	-------------

On-Board Controls	<i>None</i>
-------------------	-------------

Windscreen	Foam (Included)
------------	-----------------

Performance

Frequency Range	60 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	100 dB SPL
-------------	------------

Sensitivity	-36 dB
-------------	--------

Signal-to-Noise Ratio	70 dB
-----------------------	-------

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRS Male (on Mic)
----------------------------	--

Headphone Connector	<i>None</i>
---------------------	-------------

Power

Bus Power	<i>None</i>
-----------	-------------

Operating Voltage	Not Specified by Manufacturer
-------------------	-------------------------------

Physical

Included Case	<i>None</i>
---------------	-------------

Included Filters	<i>None</i>
------------------	-------------

Operating Temperature	32 to 122°F / 0 to 50°C
-----------------------	-------------------------

Storage Temperature	-4 to 140°F / -20 to 60°C
---------------------	---------------------------

Packaging Info

Package Weight	0.12 lb
----------------	---------

Box Dimensions (LxWxH)	4 x 2.6 x 1.1"
------------------------	----------------
