

Comica Audio CVM-V01.USB Specs

Microphone

| | |
|------------------------|--|
| Primary Applications | Podcast, Web-Streaming, Recording to Mobile Device, ENG (Electronic News Gathering), Audio for Video, Conferencing |
| Form Factor | Lavalier |
| Intended Sound Sources | Speech/Voice Over |
| Sound Field | Mono |
| Capsule | 1 x Electret Condenser |
| Polar Pattern | Omnidirectional |
| Circuitry | Solid-State |
| High-Pass Filter | <i>None</i> |
| Gain Adjustment | <i>None</i> |
| Windscreen | Metal Mesh (Included) |

Performance

| | |
|-----------------|-----------------|
| Frequency Range | 60 Hz to 20 kHz |
|-----------------|-----------------|

| | |
|-------------|--------|
| Sensitivity | -32 dB |
|-------------|--------|

Connectivity

| | |
|----------------------------|-------------|
| Output Connectors (Analog) | <i>None</i> |
|----------------------------|-------------|

| | |
|-----------------------------|--|
| Output Connectors (Digital) | 1 x USB Type-C Male (on Attached Cable) |
|-----------------------------|--|

| | |
|---------------------|--------------------------|
| Headphone Connector | 1 x 1/8" / 3.5 mm |
|---------------------|--------------------------|

| | |
|--------------|---------------|
| Cable Length | 8.20' / 2.5 m |
|--------------|---------------|

| | |
|-----------------------|-------------|
| Wireless Connectivity | <i>None</i> |
|-----------------------|-------------|

| | |
|-----------|-------------|
| Bluetooth | <i>None</i> |
|-----------|-------------|

Digital Audio

| | |
|----------------|--------|
| A/D Conversion | 24-Bit |
|----------------|--------|

| | |
|-------------|--------|
| Sample Rate | 48 kHz |
|-------------|--------|

| | |
|--------------------------|-------------|
| Operating System Support | <i>None</i> |
|--------------------------|-------------|

| | |
|----------------|---------|
| Available Port | USB 2.0 |
|----------------|---------|

Power

Bus Power

USB

Operating Voltage

Not Specified by Manufacturer

Physical

Mounting

Alligator Clip (Included)

Included Case

Pouch

Included Filters

None

Operating Temperature

32 to 122°F / 0 to 50°C

Storage Temperature

-4 to 140°F / -20 to 60°C

Dimensions

H: 1.7 x W: 0.4 x L: 1.1" / H: 42 x W: 11 x L: 29 mm
(Control Module)

Weight

1 oz / 28 g

Packaging Info

Package Weight

0.195 lb

Box Dimensions (LxWxH)

5.7 x 5 x 1.7"

