

Comica Audio CVM-D02 Specs

Microphone

Form Factor	Lavalier
Sound Field	Mono
Capsule	2 x Electret Condenser
Polar Pattern	Omnidirectional
Circuitry	Solid-State
High-Pass Filter	<i>None</i>
Gain Adjustment	<i>None</i>
Windscreen	Foam, Windsock/Windjammer (Included)

Performance

Frequency Range	50 Hz to 20 kHz
Maximum SPL	100 dB SPL (1 kHz)
Impedance	600 Ohms

Sensitivity	-35 dB at 1 kHz
-------------	-----------------

Dynamic Range	114 dB
---------------	--------

Signal-to-Noise Ratio	68 dB SPL
-----------------------	-----------

THD	< 5%
-----	------

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRS Male (on Attached Cable) 1 x 1/8" / 3.5 mm TRRS Male (with Included Adapter)
----------------------------	---

Cable Length	8.20' / 2.5 m (Straight)
--------------	--------------------------

Cable Diameter	0.098" / 2.5 mm
----------------	-----------------

Power

Operating Voltage	Not Specified by Manufacturer
-------------------	-------------------------------

Physical

Mounting	Alligator Clip
----------	----------------

Construction Material	Aluminum
-----------------------	----------

Packaging Info

Package Weight 0.3 lb

Box Dimensions (LxWxH) 6.5 x 3 x 1.9"
