

Specifications

MODEL		X554HB
LCD MODULE		
Viewable size (diagonal)		54.6"/ 1,388 mm
Active screen area (W × H)		1,209.6 × 680.4 mm
Panel technology		S-PVA
Native resolution		1,920 × 1,080
Brightness (factory setting / maximum)		2,000 / 2,700 cd/m ²
Contrast ratio (typical)		5,000:1 (Native contrast)
Viewing angle [°]		178 horizontal / 178 vertical (at CR>10)
Response time (typical)		6 ms (G to G)
Backlight		Direct LED backlight
CONNECTIVITY		
Input terminals	DisplayPort	DisplayPort × 1
	HDMI	HDMI × 1
	DVI	DVI-D × 1
	VGA	Mini D-sub 15pin × 1
	Audio	Digital: HDMI × 1, DisplayPort × 1, Analog: 3.5 mm Stereo mini jack × 2
Output terminals	DisplayPort	DisplayPort × 1
	Audio	3.5 mm Stereo Mini Jack × 1
External control	RS232C	D-Sub 9 pin × 1
	Ethernet	RJ-45 10 / 100BASE-T × 2 (In/out)
	Remote in	3.5 mm Stereo Mini Jack × 1
	Remote out	Possible via Ethernet
	DDC/CI	Mini D-sub 15 pin / DVI-D

MODEL		X554HB
Service port		USB Type A × 1
Option slots	Expansion slots	Open pluggable specification (NEC / Intel OPS standard) × 1, Interface extension × 1
Speaker output	External speakers	15 W + 15 W (8 Ω)
	Internal speakers	10 W + 10 W
POWER		
Power requirement		6.3 A @ 100-120 V, 2.4 A @ 220-240 V
Power consumption (typical)		310 W
Power consumption (standby mode)		< 0.5 W
PHYSICAL SPECIFICATIONS		
Bezel width (L/R, T/B)		19.5 mm
Dimensions (without stands: W × H × D)		1,253.6 × 724.4 × 137.7 mm
Dimensions (with stands and handles: W × H × D)		1,253.6 × 760.7 × 400.0 mm
Packaging dimensions (W × H × D)		1,470 × 965 × 430 mm
Net weight (without stands)		32.6 kg
Gross weight (with box)		42.2 kg
VESA compatible mounting interface		400 × 400 mm (M8, 4 holes)
Supported orientation		Landscape, Portrait
ENVIRONMENTAL CONDITIONS		
Operating temperature		0°C to 40°C
Operating humidity		20% to 80% (without condensation)
ADDITIONAL FEATURES		
Operating hours		24 / 7

MODEL		X554HB
Sensors	Ambient light sensor	Integrated, triggered actions programmable
	Motion sensor	Optional, external, 4 – 5 m range, triggered actions programmable
	Temperature sensor	Integrated, 3 sensors, triggered actions programmable
	NFC sensor	Integrated, 2-cm range, free NEC Android App required
ACCESSORIES		
Included		Power cord, DVI-D cable, IR remote control, Batteries, Setup manual, Clamp × 3, Screw with washer × 3, Thumbscrew for optional stand × 2, CD-ROM