

Shure Beta 52A Specs

Microphone

Primary Applications	Live Sound, Studio Recording
----------------------	------------------------------

Form Factor	Stand/Boom Mount
-------------	------------------

Intended Sound Sources	Electric Bass, Kick Drum
------------------------	--------------------------

Sound Field	Mono
-------------	------

Capsule	Dynamic
---------	---------

Polar Pattern	Supercardioid
---------------	---------------

Orientation	End Address
-------------	-------------

High-Pass Filter	<i>None</i>
------------------	-------------

Tone Adjustment	<i>None</i>
-----------------	-------------

Gain Adjustment	<i>None</i>
-----------------	-------------

Indicators	<i>None</i>
------------	-------------

On-Board Controls	<i>None</i>
-------------------	-------------

Windscreen	<i>None</i>
------------	-------------

Performance

Frequency Range 20 Hz to 10 kHz

Maximum SPL 174 dB SPL

Impedance 150 Ohms ⓘ

Sensitivity -64 dBV/Pa

Connectivity

Output Connectors (Analog) **1 x** XLR 3-Pin (on Mic)

Headphone Connector *None*

Physical

Mounting 5/8"-27 Female (via Integrated Hardware)

Construction Material Metal, Steel Wire Grille

Dimensions \varnothing : 3.75 x H: 6.41L: 4.45" / \varnothing : 95.25 x H: 162.81L: 113.03 mm

Weight 21.6 oz / 605 g
