

Shure MVL Specs

Microphone

Form Factor	Lavalier
Sound Field	Mono
Capsule	1 x MEMS
Polar Pattern	Omnidirectional
High-Pass Filter	<i>None</i>
Windscreen	Foam (Included)

Performance

Frequency Range	45 Hz to 20 kHz
Maximum SPL	124 dB SPL
Impedance	350 Ohms
Sensitivity	-44 dBFS/Pa at 1 kHz
Dynamic Range	95 dB
Signal-to-Noise Ratio	65 dB
Equivalent Noise Level	29 dB A-Weighted

Connectivity

Output Connectors (Analog)	1 x 1/8" / 3.5 mm TRRS Male (on Attached Cable)
----------------------------	---

Cable Length	52" / 1.32 m
--------------	--------------

Power

Operating Voltage	2.7 V (Plug-In Power)
-------------------	-----------------------

Operating Current Consumption	245 μ A (Plug-In Power)
-------------------------------	-----------------------------

Physical

Color	Black
-------	-------

Mounting	Alligator Clip (Included)
----------	---------------------------

Included Case	Soft Case
---------------	-----------

Construction Material	Die-Cast Zinc
-----------------------	---------------

Dimensions	\varnothing : 0.22 x L: 0.6" / \varnothing : 5.59 x L: 15.24 mm (Microphone)
------------	--

Weight	0.28 oz / 8 g
--------	---------------
