

Shure MVI-DIG Specs

Form Factor	Mobile
Display	1 x LED Touchscreen
Channels of I/O	1 Input
Max Sample Rate/Resolution	48 kHz / 24-Bit
Number of Mic Preamps	1
Input Level Adjustment	via Touchscreen
Solo/Mute	Mute per Input Channel
Expansion Slots	<i>None</i>

Connectivity

Analog Audio I/O	1 x Combo XLR-1/4" 3-Pin Balanced/Unbalanced Input 1 x 1/8" / 3.5 mm TRS Headphone Output
Phantom Power	+48 V
Digital Audio I/O	<i>None</i>
Host Connection / USB	Micro-USB (Class-Compliant)
USB (Non-Host)	<i>None</i>

Sync I/O *None*

Network I/O *None*

MIDI I/O *None*

Wireless Connectivity *None*

Memory Card Slot *None*

Performance

Frequency Response 20 Hz to 20 kHz

Gain/Trim Range
Mic:
0 dB to +36 dB
Hi-Z:
+9 dB

Max Input Level
Mic:
0 dBV
Hi-Z:
9 dBV

Impedance
Mic :
2 Kilohms
Hi-Z :
1 Megohm

Digital Audio

Sample Rates 44.1 / 48 kHz

Bit Depths 16 / 24-Bit

Compatibility

OS Compatibility	macOS 10.7 / 10.8 / 10.9 / 10.10 Windows 7 or Later iOS 7 or Later
------------------	--

Included Software	<i>None</i>
-------------------	-------------

Mobile Device Compatibility	iPhone 5, 5c, 5s, 6, 6 Plus iPad 4th Gen. iPad Air iPad Air 2 iPad Mini 1st Gen., 2nd Gen., 3rd Gen. iPod Touch 5th Gen.
-----------------------------	---

Power

Power Requirements	Lightning Bus Power, USB Bus Power
--------------------	------------------------------------

Physical

Dimensions	3.3 x 2.8 x 1.7" / 84 x 72 x 42 mm
------------	------------------------------------

Weight	10.9 oz / 310.0 g
--------	-------------------
