

Shure MV7 Specs

Microphone

Primary Applications	Podcast, Audio for Video
Form Factor	Desktop
Intended Sound Sources	Vocals
Sound Field	Mono
Capsule	1 x Dynamic
Polar Pattern	Unidirectional
Orientation	End Address
Circuitry	Solid-State
High-Pass Filter	<i>None</i>
Gain Adjustment	0 to +36 dB
On-Board Controls	Gain/Sensitivity, Headphone Volume, Mic Mute
Windscreen	Built-In

Performance

Frequency Range	20 Hz to 20 kHz
-----------------	-----------------

Maximum SPL	Unidirectional: 132 dB SPL ⓘ
Impedance	Unidirectional: 314 Ohms at 1 kHz ⓘ
Sensitivity	Unidirectional: -55 dBV at 1 kHz Unidirectional: -47 dBFS/Pa at 1 kHz ⓘ

Connectivity

Output Connectors (Analog)	1 x XLR 3-Pin Male (on Mic)
Output Connectors (Digital)	1 x USB Type-B Female (on Mic)
Headphone Connector	1 x 1/8" / 3.5 mm
Cable Length	10' / 3.0 m (Straight)

Digital Audio

A/D Conversion	16 / 24-Bit
Sample Rate	Up to 44.1 / 48 kHz
Operating System Support	Android, Windows, iOS, macOS/OS X
Mobile Device Compatibility	iPad or Later iPhone 6th Gen. or Later iPod
RAM Requirement	2 GB Minimum

Power

Bus Power

USB / Lightning

Physical

Color

Silver

Mounting

5/8"-27 Female (via Integrated Hardware)

Construction Material

Metal

Dimensions

ø: 2.6 x L: 2.1" / ø: 66.5 x L: 53.6 mm (Microphone)
H: 6.5 x W: 3.6 x L: 6" / H: 164 x W: 90.2 x L:
153.6 mm (Microphone, with Mount)

Weight

1.21 lb / 0.55 kg
