

ClearOne 910-158-500 Specs

Speaker

Frequency Response	200 Hz to 3.3 kHz
--------------------	-------------------

Maximum Sound Pressure Level (SPL)	90 dBA at 1' / 30.5 cm
------------------------------------	------------------------

Total Harmonic Distortion (THD)	0.01%
---------------------------------	-------

Microphone

Frequency Response	200 Hz to 3.3 kHz
--------------------	-------------------

Impedance	1000 Ohms
-----------	-----------

Technology

Duplex Mode	Echo Cancellation
-------------	-------------------

Active Noise Cancellation	No
---------------------------	----

Connectivity

Audio Ports	1 x 2.5 mm TS
-------------	----------------------

Telephone Ports	1 x RJ11
-----------------	-----------------

Display

Touchscreen *None*

Environmental

Operating Temperature 32 to 118°F / 0 to 48°C

Operating Humidity 15 to 80%

Storage Temperature 41 to 158°F / 5 to 70°C

Storage Humidity 10 to 90%

Certifications FCC, UL, as per Manufacturer

Physical

Dimensions 10.5 x 10.5 x 3.0" / 26.7 x 26.7 x 7.6 cm (Handset)
4.2 x 5.5 x 2.5" / 10.8 x 14.0 x 6.4 cm (Base)

Weight 2.7 lb / 1.2 kg (Handset)
0.6 lb / 0.27 kg (Base)
