

SKU: C11CJ11401

[CLOSE ALL](#)

Technology

Printing Method	Impact dot matrix
Number of Pins	24 pins
Number of columns	94 columns
Pins	24 Needles (2 x 12)

Print

Printing Speed	HighSpeed-Draft: 480 cpi: 10 chars/s, Draft: 360 cpi: 10 chars/s, LQ: 120 cpi: 10 chars/s, Ultra Speed-Draft: 540 cpi: 10 chars/s
Barcodes	Coda bar (NW-7), Code 128, Code 39, EAN-13, EAN-8, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	6 plus one original
Character Sets	14
Character Tables	PCAPTEC, PC437, PC708, PC720, PC850, PC858, PC864, PCAR864, ISO-8859-15, Roman 8, Italic

Connectivity

Interfaces

Bidirectional parallel, RS-232, Hi-Speed USB - compatible with USB 2.0 specification, IEEE 1284

Paper / Media Handling

Document Feed

Single sheet front, Continuous media front, Paper output front and rear

Paper Formats

Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer)

Paper Thickness Multi Part

0.12 mm - 0.53 mm

Paper Thickness Single Sheet

0.065 mm - 0.19 mm

General

Power consumption

61 Watt, 0.7 Watt (standby)

Supply Voltage

AC 220 V - 240 V, 50 Hz - 60 Hz

Product dimensions

384 x 280 x 203 mm (Width x Depth x Height)

Product weight

7.8 kg

Supported Temperature

Operation 5° C - 38° C

Supported Humidity

Operation 10% - 85%

Mean Time Between Failures

35,000 hours

Print Head Life	400 Million Strokes/Wire
Noise	Operation: 55 dB (A)- Standby: 52 dB (A)
Fonts	Bitmap font EPSON Courier (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON Draft (10 CPI, 12 CPI, 15 CPI), Bitmap font EPSON OCR-B (10 CPI), Bitmap font EPSON Orator (10 CPI), Bitmap font EPSON Orator-S (10 CPI), Bitmap font EPSON Prestige (10 CPI, 12 CPI), Bitmap font EPSON Roman (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Sans Serif (10 CPI, 12 CPI, 15 CPI, Proportional), Bitmap font EPSON Script (10 CPI), Bitmap font EPSON Script C (Proportional), Scalable font EPSON Roman T, Scalable font EPSON Sans Serif H
Noise Level	Operation: 55 dB (A)
What's in the box	Power cable, Ribbon, Setup guide, User manual (CD)

Other Features

Emulations	IBM PPDS, PR2, ESC/P2
Input Data Buffer	128 kB
