

SKU: C11CH59403

[CLOSE ALL](#)

## Technology

<b>Printing Method</b>	Impact dot matrix
<b>Number of Pins</b>	24 pins
<b>Number of columns</b>	136 columns
<b>Pins</b>	24 Needles

## Print

<b>Printing Speed</b>	Draft: 10 cpi: 550 chars/s, HighSpeed-Draft: 10 cpi: 550 chars/s, LQ: 10 cpi: 195 chars/s
<b>Barcodes</b>	Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E
<b>Carbon Copies</b>	7 plus one original
<b>Character Tables</b>	PCAPTEC, PC437, PC720, PC850, PC858, PC864, PCAR864, ISO-8859-1, ISO-8859-15, Roman 8, Italic

## Paper / Media Handling

<b>Document Feed</b>	Single sheet rear, Continuous media rear, Paper output rear, bulk measurement: yes
----------------------	--

<b>Paper Formats</b>	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Envelopes, Cardboard
<b>Paper Thickness Continuous Paper</b>	0.12 mm - 0.62 mm
<b>Paper Thickness Label Total Sheet</b>	0.16 mm - 0.19 mm
<b>Paper Thickness Multi Part</b>	0.12 mm - 0.62 mm
<b>Paper Thickness Single Sheet</b>	0.065 mm - 0.19 mm

---

## General

<b>Power consumption</b>	78 Watt, 0.8 Watt (standby)
<b>Supply Voltage</b>	AC 100 V - 240 V, 50 Hz - 60 Hz
<b>Product dimensions</b>	661 x 433 x 276 mm (Width x Depth x Height)
<b>Product weight</b>	18.9 kg
<b>Supported Temperature</b>	Operation 5° C - 35° C
<b>Supported Humidity</b>	Operation 10% - 80%
<b>Compatible Operating Systems</b>	Windows 10, Windows 7, Windows 8, Windows XP
<b>Included Software</b>	Epson Status Monitor
<b>Mean Time Between Failures</b>	10,000 hours

<b>Print Head Life</b>	200 Million Strokes/Wire
<b>Noise</b>	Operation: 59 dB (A)
<b>Memory</b>	128 MB Included
<b>Noise Level</b>	Operation: 59 dB (A)
<b>Ribbon Yield</b>	9000000 characters Black Draft

---

## Other Features

<b>Input Data Buffer</b>	128 kB
--------------------------	--------

---