

SKU: C11CF39401

[CLOSE ALL](#)

Technology

Printing Method	Impact dot matrix
Number of Pins	24 pins
Number of columns	80 columns
Pins	24 Needles

Print

Printing Speed	Ultra Speed-Draft: 10 cpi: 550 chars/s, HighSpeed-Draft: 10 cpi: 487 chars/s, 12 cpi: 584 chars/s, Draft: 10 cpi: 366 chars/s, LQ: 10 cpi: 121 chars/s
Barcodes	Code 128, Code 39, EAN-13, EAN-8, Interleaved 2 of 5, POSTNET, UPC-A, UPC-E
Carbon Copies	6 plus one original
Character Tables	PC437, PC708, PC720, PC850, PC858, PC864, PCAR864, ISO-8859-15, Roman 8, Italic

Connectivity

Interfaces	Hi-Speed USB - compatible with USB 2.0 specification, Parallel
-------------------	--

Paper / Media Handling

Document Feed	Single sheet front and rear, Continuous media front and rear, Paper output rear
Paper Formats	Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes, Cardboard
Paper Thickness Continuous Paper	0.065 mm - 0.49 mm
Paper Thickness Label Base Sheet	0.16 mm - 0.19 mm
Paper Thickness Multi Part	0.12 mm - 0.46 mm
Paper Thickness Single Sheet	0.065 mm - 0.14 mm

General

Product dimensions	437 x 375 x 177 mm (Width x Depth x Height)
Product weight	7.2 kg
Supported Temperature	Operation 5° C - 35° C
Supported Humidity	Operation 10% - 80%
Compatible Operating Systems	Windows 10, Windows 7, Windows 7 x64, Windows 8, Windows 8.1, Windows 8.1 x64 Edition, Windows Server 2012 R2, Windows Vista, Windows Vista x64, Windows XP

Mean Time Between Failures	25,000 hours
Print Head Life	400 Million Strokes/Wire
Noise Level	Operation: 55 dB (A)
Ribbon Yield	5000000 characters Black Draft

Other Features

Emulations	ESC/P2
Input Data Buffer	128 kB
