

Tech Specs

Product features and specifications are subject to change without prior notice.

SKU: C11C641001

[CLOSE ALL](#)

Technology

Printing Method	Impact dot matrix
Number of Pins	9 pins
Number of columns	136 columns
Pins	9 Needles

Print

Printing Speed	HighSpeed-Draft: 10 cpi: 300 chars/s, 12 cpi: 337 chars/s, Draft: 10 cpi: 225 chars/s, 12 cpi: 270 chars/s, NLQ: 10 cpi: 56 chars/s, 12 cpi: 67 chars/s
Carbon Copies	4 plus one original
Printing Resolution	240 x 144 DPI

Connectivity

Interfaces USB 2.0 Type B, Bidirectional parallel, RS-232

Paper / Media Handling

Document Feed Single sheet rear, Continuous media rear, Paper output rear, Optional Automatic Document Feed (CSF): 50

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes

General

Power consumption 23 Watt

Product dimensions 546 x 275 x 164 mm (Width x Depth x Height)

Product weight 6.6 kg

Supported Temperature Operation 5° C - 35° C, Storage 5° C - 35° C

Supported Humidity Operation 10% - 80%, Storage 10% - 80%

Compatible Operating Systems Windows 2000, Windows 7, Windows 8, Windows 98, Windows Server 2008 R2, Windows XP

Included Software Epson Status Monitor

Mean Time Between Failures	6,000 hours
Print Head Life	400 Million Strokes/Wire
Noise	Operation: 49 dB (A)
Memory	64 kB Included
Ribbon Yield	3000000 characters Black Draft
What's in the box	Driver and utilities (CD), Main unit, Power cable, Ribbon, Setup guide, Software (CD), User manual (CD), Warranty document
