

Tech Specs

Product features and specifications are subject to change without prior notice.

SKU: C11C526022A0

CLOSE ALL

Technology

Printing Method	Impact dot matrix
Number of Pins	9 pins
Number of columns	136 columns
Pins	18 Needles (2 x 9)

Print

Printing Speed	HighSpeed-Draft: 10 cpi: 566 chars/s, 12 cpi: 680 chars/s, Draft: 10 cpi: 419 chars/s, NLQ: 10 cpi: 104 chars/s
Carbon Copies	6 plus one original
Printing Resolution	240 x 144 DPI

Connectivity

Interfaces Bidirectional parallel, Wired Network, USB 2.0 Type B, Type B interface

Paper / Media Handling

Paper Formats Sheet Paper (single- and multi-layer), Continuous Paper (single- and multi-layer), Labels (single- and multi-layer), Roll Paper, Envelopes, Cardboard

General

Power consumption 53 Watt, 45 Watt (standby)

Product dimensions 589 x 350 x 168 mm (Width x Depth x Height)

Product weight 9.4 kg

Supported Temperature Operation 5° C - 35° C

Supported Humidity Operation 10% - 80%

Compatible Operating Systems Windows 2000, Windows 7, Windows 8, Windows 98, Windows XP

Included Software Epson Status Monitor

Mean Time Between Failures 20,000 hours

Print Head Life	400 Million Strokes/Wire
Noise	Operation: 55 dB (A)
Memory	128 kB Included
Ribbon Yield	12000000 characters Black Draft
What's in the box	Driver and utilities (CD), External network interface, Main unit, Power cable, Ribbon, Setup guide, Software (CD), User manual (CD), Warranty document

Other Features

Emulations	ESC/P, IBM PPDS, IBM PPDS/ML
-------------------	------------------------------
