

Yamaha MG06 Specs

Input Channels	2 x XLR-1/4" Combo (Mic/Line) 2 x 1/4" / 6.3 mm Stereo (Line)
Phantom Power	+48 V Switchable, Channels 1, 2
Output Channels	2 x XLR Stereo 2 x 1/4" / 6.3 mm Stereo 1 x 1/4" / 6.3 mm Headphone
Bus	1 x 1/4" / 6.3 mm Stereo
Pad	26 dB (Mono Channels)
HPF	80 Hz, 12 dB/Oct (Mono Channels)
Equalizer	EQ High (Mono Channels) Gain: ± 15 dB, Frequency: 10 kHz Shelving EQ Low (Mono Channels) Gain: ± 15 dB, Frequency: 100 Hz Shelving

LED	LED Turns On When Post EQ Signal Reaches 3 dB Below Clipping
Level Metering	2 x 7-Segment LED Meter (Peak, +6, +3, 0, -3, -10, -20 dB)
Total Harmonic Distortion	0.01% @ +8 dBu (20 Hz to 20 kHz), Gain Knob: Min, 0.003% @ +18 dBu (1 kHz), Gain Knob: Min
Frequency Response	20 Hz to 20 kHz \pm 0.5 dB, Refer to the Nominal Output Level @ 1 kHz, Gain Knob: Min
Equivalent Input Noise	-128 dBu (Mono Input Channel, Rs: 150 Ohms, Gain Knob: Max)
Residual Output Noise	-102 dBu (Stereo Out, Stereo Level Knob: Min)
Crosstalk	-88 dB
Power Requirements	PA-130 (12 VDC / 1 A), 120 VAC, 60 Hz MU18 (12 VDC / 1.5 A), 100-240 VAC, 50/60 Hz Or Equivalent Recommended by Yamaha
Power Consumption	12 W

Dimensions 5.9 x 2.4 x 7.9" / 149 x 62 x 202 mm

Net Weight 1.98 lb / 0.9 kg

Packaging Info

Package Weight 3.27 lb

Box Dimensions (LxWxH) 10.65 x 9.65 x 4.8"
