

Yamaha DZR15 Specs

PA Speaker

Configuration Active 2-Way

Enclosure Type Bass-Reflex Loudspeaker

Total Power Capacity 2000 W Peak
950 W RMS

Amplifier Power Rating **LF:**
1000 W Peak
850 W RMS
HF:
1000 W Peak
100 W RMS

Amplifier Class Class-D

Drivers

HF Driver **1 x** Rotatable Horn Titanium Compression Driver with 1" / 25.4 mm Throat

HF Voice Coil 2" / 50.8 mm

LF Driver **1 x** 15" / 381 mm Woofer

LF Voice Coil 3" / 76.2 mm

Magnet **HF:**
Neodymium
LF:
Neodymium

Performance

Frequency Range 34 Hz to 20 kHz -10 dB

Maximum SPL 139 dB

Coverage Angle 90° H x 50° V (Rotatable Horn)
50° H x 90° V (Monitor)

Max Input Level **Line Input:**
+24 dBu

I/O Impedance

Input:
20 Kilohms

Connectivity

Audio I/O

2 x Combo XLR-1/4" TRS Input
2 x XLR 3-Pin Output

USB

1 x USB Type-A (External Memory, Host Connection)

Signal Processing

Crossover

1.7 kHz

Max Sample Rate/Resolution

96 kHz

Power

AC Input Power

Universal:
100 to 240 VAC, 50 / 60 Hz

AC Power Connector **1 x** IEC (Locking)

Power Consumption 45 W (Idle)
150 W (1/8 Power)

Physical

Mounting **12 x** M10 Fly Point
2 x 1.4" / 35 mm Pole Socket (Dual Angle, Bottom)

Handles **1 x** Each Side

Cooling Fan (Variable Speed)

Construction Material Plywood

Dimensions 17.7 x 30 x 18.1" / 450 x 761 x 460 mm

Weight 55.6 lb / 25.2 kg

Packaging Info

Package Weight

70 lb

Box Dimensions (LxWxH)

35 x 22 x 21.75"
