

Yamaha DBR10 Specs

PA Speaker

Configuration Active 2-Way

Enclosure Type Bass-Reflex Loudspeaker

Total Power Capacity 700 W Peak
325 W RMS

Amplifier Power Rating **LF:**
500 W Peak
260 W RMS
HF:
200 W Peak
65 W RMS

Drivers

HF Driver **1 x 1" / 25 mm Compression Driver**

LF Driver **1 x 10" / 25.4 cm Woofer**

LF Voice Coil **2" / 5.1 cm**

Magnet **HF:**
Ferrite
LF:
Ferrite

Performance

Frequency Range **55 Hz to 20 kHz -10 dB**

Maximum SPL **129 dB SPL**

Coverage Angle **90° H x 60° V**

Connectivity

Audio I/O **2 x Combo XLR-1/4" TRS Input**
1 x Stereo RCA Unbalanced Line Input
1 x XLR 3-Pin Output

Signal Processing

Crossover	2.1 kHz
-----------	---------

Power

AC Input Power	100 to 120 VAC, 50 / 60 Hz
----------------	----------------------------

Power Consumption	60 W (1/8 Power) 18 W (Idle)
-------------------	---------------------------------

Physical

Mounting	1 x 1.38" / 35 mm Pole Socket (Bottom) 1 x Pole Socket 2 x M8 (Bottom)
----------	---

Handles	1 x Top
---------	----------------

Cooling	Fan (Variable Speed)
---------	----------------------

Construction Material	Plastic
-----------------------	---------

Dimensions	12.1 x 19.4 x 11.4" / 308 x 493 x 289 mm
------------	--

Weight	23.2 lb / 10.5 kg
--------	-------------------

Packaging Info

Package Weight	30.75 lb
----------------	----------

Box Dimensions (LxWxH)	22.6 x 15.8 x 14.9"
------------------------	---------------------
