

Yamaha DBR15 Specs

PA Speaker

Configuration	Active 2-Way
Enclosure Type	Bass-Reflex Loudspeaker
Total Power Capacity	1000 W Peak 465 W RMS
Amplifier Power Rating	LF: 800 W Peak 400 W RMS HF: 200 W Peak 65 W RMS

Drivers

HF Driver	1 x 1.4" / 35.6 mm Compression Driver
-----------	--

LF Driver **1 x 15" / 387 mm Woofer**

LF Voice Coil **2.5" / 6.35 cm**

Magnet **HF:**
Ferrite
LF:
Ferrite

Performance

Frequency Range **50 Hz to 20 kHz -10 dB**

Maximum SPL **132 dB SPL**

Coverage Angle **90° H x 60° V**

Connectivity

Audio I/O **2 x Combo XLR-1/4" TRS Input**
1 x Stereo RCA Unbalanced Input
1 x XLR 3-Pin Output

Signal Processing

Crossover 2.1 kHz

Power

AC Input Power 100 to 120 VAC, 50 / 60 Hz

Power Consumption 74 W (1/8 Power)
18 W (Idle)

Physical

Mounting **1 x** 1.38" / 35 mm Pole Socket (Bottom)
2 x M8 (Bottom)
1 x M8 (Rear)
1 x Pole Socket

Handles **2 x** Side

Cooling Fan (Variable Speed)

Construction Material

Plastic

Dimensions

17.9 x 27.6 x 14.9" / 455 x 700 x 378 mm

Weight

42.6 lb / 19.3 kg

Packaging Info

Package Weight

53.5 lb

Box Dimensions (LxWxH)

31 x 21 x 19"

